

22" LED monitor with PoE

HDMI™

- 22" LED monitor
- 16:9
- Native resolution of 1920 x 1080
- 2 HDMI, 1 VGA
- Audio input / output
- 24x7 operation
- VESA 75x75
- MTBF of 50,000 hours
- Supports PoE



Reference / Model

HYU-459-POE / HYU-459-POE

22" LED monitor

16:9 aspect ratio

Supports PAL, NTSC and SECAM with auto detection

Native resolution: 1920x1080

Brightness: 350 cd/m²

Contrast 1000:1

24-bit color depth (16.7 million colors)

Pixel size: 0.248x0.248

Viewing angle: 178°/178° (horizontal/vertical)

Response time: 5 ms

High-fidelity digital processing, bright and vivid video

Digital 3D noise reduction technology

Digital 3D filtering

22" LED monitor with PoE

Reference / Model	HYU-459-POE / HYU-459-POE
	OSD control: Auto adjustment, brightness, contrast, horizontal/vertical position, clock, phase, color, language, etc.
	Input interface: 2 HDMI (2.0), 1 VGA, 1 USB
	Audio input/output
	Extended operating temperature from -30°C ~ +85°C
	Power supply: 12V ~ 24V DC, 50/60Hz
	Power consumption: ≤20W
	Support PoE input
	Support LAN output
	VESA 75x75 mounting pattern
	Dimensions: 476.64(W) x 268.11(H) mm
	Supports 24x7 operation
	MTBF: 50,000 hours