

HYU-1060

SF-XVR6104S

HYUNDAI

HYUNDAI 5-in-1 4-channel ZVR



COAXIAL
AUDIO

HDCVI™

HDTVI

AHD

CVBS

H.265+



aiSense

MOTION
DETECTION 2.0

- ZVR 5 in 1 HYUNDAI 4 channels
- H.265+/H.265 formats
- 4 BNC channels + 1 IP channel
- Recording 1080PLite@25/30ips
- Simultaneous HDMI and VGA outputs
- Bidirectional audio, coaxial audio
- 4 inputs / 1 alarm output
- Supports 1 HDD 4TB, 1 RJ45, 2 USB, 12V DC.



Reference / Model

HYU-1060 / SF-XVR6104S

ZVR 5 in 1 of 4 HD analog channels + 1 IP channel

5 technologies: IP Cameras, HDCVI, HDTVI, AHD and analog CVBS

H.265 Pro+, H.265 Pro, H.265, H.264+, H.264, H.264 video format

4 BNC inputs (supports coaxitron):

HDCVI: 1080P, 720P

HDTVI: 1080P, 720P

AHD: 1080P, 720P

analog CVBS: 960H, PAL/NTSC

1 IP input (4+1) 1080P

Simultaneous HDMI (1080P) and VGA (1080P) outputs

Audio channels: 1 RCA audio input / 1 RCA audio output

Bi-directional audio: via RCA audio channel 1

4 audio inputs via coaxial cable

HYUNDAI 5-in-1 4-channel ZVR

Reference / Model	HYU-1060 / SF-XVR6104S
Recording resolution:	1080P Lite, 720P Lite, WD1, 4CIF, VGA, CIF
Main stream:	
1080P mode:	1080P Lite, 720P Lite, WD1, 4CIF, VGA, CIF (25/30 ips).
720P mode:	720P, WD1, 4CIF, VGA, CIF (25/30 fps)
Standard mode:	WD1, 4CIF, VGA, CIF (25/30 fps)
Secondary stream:	4CIF (15 fps), CIF, QVGA (25/30 fps)
4-channel synchronized playback	
Long distance HDTV transmission:	up to 1200 meters at 720P and 800 meters at 1080P
Internal capacity for 1 SATA HDD	up to 4TB (sold separately)
Intelligent search	
Deep learning based motion detection 2.0	is enabled by default for all analog channels, it can classify people and vehicles and minimize false alarms caused by lights or objects such as leaves.
4 alarm inputs / 1 alarm output	
Auto-adaptive Ethernet RJ45 (10/100M) network interface	
Network protocols:	TCP/IP, PPPoE, DHCP, HYU-Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS
Remote access	for up to 32 users
P2P in the cloud, DDNS DEMES, Push and zero channel	
Connections:	2 USB 2.0
Power supply:	12V DC, 1.5A
Power consumption:	≤16W (excluding HDD)
Operating temperature:	-10°C ~ +55°C
Relative humidity:	10~90%.
Dimensions:	260 (W) x 45 (H) x 222 mm (desktop)
Weight:	800 g