

# HYU-935

SF-IPT943CWA-4P

HYUNDAI

## IP dome HYUNDAI Color View 4MP outdoor

**4MP** **Value Line** **IP67** **STARLIGHT FULL-Color** **120 dB WDR** **H.265+**

- HYUNDAI NEXT GEN Color View IP Dome
- 4MP@20ips, H.265+/H.265
- Color 24/7, 0.001 lux, Smart Light 30m
- 2.8mm optics
- WDR 120dB, 3D-DNR, 1 ROI
- RJ45, Onvif, IP67, 3AXIS, PoE.



Reference / Model

HYU-935 / SF-IPT943CWA-4P

Specifications

**IP dome HYUNDAI Color View 4MP outdoor****Reference / Model****HYU-935 / SF-IPT943CWA-4P**

1/2.7" 4 megapixel CMOS sensor  
Compression formats: H.265+, H.265, H.264+, H.264, MJPEG  
Digital resolution: 4MP (2560x1440), 3MP (2304x1296), 1080P (1920x1080), 720P (1280x720), VGA (640x480), Q720P (640x360), QVGA (320x240)  
Stream 1: 4MP (20fps), 3MP, 1080P, 720P (25fps)  
Stream 2: VGA, Q720P, QVGA (25fps)  
24/7 color mode  
Smart Light: White light with a range of 30 meters  
0.001lux F1.0  
2.8mm fixed lens  
View Angle: 102°(H), 54°(V), 121°(D)  
Image modes: BLC, HLC, WDR 120dB, 3D-DNR, Mirror  
1 fixed ROI zone main stream  
Video sensor and privacy mask  
Image rotation, brightness, saturation, contrast, sharpness, gain control and white balance adjustment via client software and web browser  
Network interface: RJ45 (10/100M)  
Network Protocols: TCP/IP, ICMP, HTTP, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP™, SMTP, IGMP, QoS, IPv6, UDP, Bonjour, SSL/TLS  
ONVIF (S/G/T), ISAPI and SDK compliant  
Up to 32 users and 6 simultaneous views  
Remote viewing via IE, Chrome and Firefox browsers  
Plug&Play connection with NEXTGEN NVR  
Compatible with DDNS DEMES  
Power supply: 12V DC (±25%), 0.37A  
Consumption: 4.5W  
Supports PoE (802.3af)  
PoE consumption: 4.5W  
Storage temperature -30°C ~ +60°C  
Operating temperature -30°C ~ +60°C  
Relative humidity: 95% (non-condensing)  
Degree of protection IP67  
metal and plastic casing  
Dimensions: Ø110 x 100.8 (H) mm  
Weight: 350g  
3AXIS: 0°~360°(PAN), 0°~75°(TILT), 0°~360°(ROT)