

HYU-834

SF-VIDISP01-7W2

HYUNDAI

Indoor two-wire HYUNDAI IP monitor



- Indoor two-wire HYUNDAI IP monitor
- Supports WiFi 7 "(1024x600) color capacitive touch screen
- Touch buttons
- Built-in microphone and speaker
- Two-wire network interface
- Alarm: 8 inputs / 2 outputs
- RS485.



Reference / Model

HYU-834 / SF-VIDISP01-7W2

Two-wire cable for power and network access

User friendly design

7" color touch screen with 1024x600 resolution

2-channel transmission plan

Store messages and capture images on SD card

Remote unlock through client or mobile software

Live image display of video intercom stations and connected cameras

Supports wireless network

Specs

128MB memory

16MB flash memory (32MB hardware support)

Embedded Linux operating system

7" capacitive touch TFT display (1024x600)

Indoor two-wire HYUNDAI IP monitor

Reference / Model	HYU-834 / SF-VIDISP01-7W2
	It incorporates omnidirectional microphone
	Incorporates speaker
	Volume configurable in local mode or by management software
	G.711U audio compression
	Noise suppression and echo cancellation
	Broad R-Reach wired network
	Two-wire network interface
	It incorporates WiFi 802.11b / g / n
	Network protocol: TCP / IP, SIP, RTSP
	8 alarm inputs
	2 relay outputs
	SD card slot up to 32GB (card not included)
	RS485 port
	2-wire power interface
	Consumption: $\leq 6W$
	Operating temperature: $-10^{\circ} C \sim + 55^{\circ} C$
	Operating Humidity: 10% ~ 90%
	Dimensions: 200 (W) x 140 (H) x 23.6 mm
	Weight: 355g