

HYU-925

HYU-925

HYUNDAI

IP fixed dome with Smart IR of 30m for outdoor



- HYUNDAI Next Gen IP fixed dome with Smart IR of 30m for outdoor
- 1/3 "CMOS of 4MP
- Dual stream
- H.265, H.264 and MJPEG compression formats
- Resolution up to 4MP at 20ips
- ICR filter
- 0.01 lux F2.0
- 2.8 mm (98 °) fixed lens
- OSD, AWB, AGC, BLC, WDR 120dB, 3D-DNR, ROI, video sensor and privacy masks
- Onvif, ISAPI
- IP67
- 3AXIS
- 12V DC
- Supports PoE



Reference / Model

HYU-925 / HYU-925

specs

IP fixed dome with Smart IR of 30m for outdoor**Reference / Model****HYU-925 / HYU-925**

Image sensor 1/3 "4 megapixel CMOS
Resolution: 4MP (2560x1440), 3MP (2304x1296), 1080P (1920x1080), 720P (1280x720), VGA (640x480), VGA (640x360)
H.265, H.264 and MJPEG video compression
Stream 1: 4MP (20 ips), 3MP, 1080P, 720P (25 ips)
Stream 2: VGA (25 ips)
Day / night mode with removable mechanical filter (ICR)
0.01 lux F2.0 (color, AGC On), 0 lux IR On
Smart IR: 30 meters
2.8mm fixed lens
Viewing angle: 98 ° (H), 53.1 ° (V), 114.7 ° (D)
Imaging modes: BLC, WDR 120dB, 3D-DNR
Image settings: Saturation, brightness, contrast, sharpness, gain and white balance adjustable through client software or web browser
Supports video sensor, 1 region of interest (ROI) to stream 1 and privacy mask
Network interface: RJ45 (10 / 100M) self-adaptive
Network protocols: TCP / IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP™, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour, IPv4, UDP, SSL / TLS
Remote viewing with browsers (IE10 +, Chrome 57+, Firefox 52+) and IOS and Android smartphones
ONVIF and ISAPI compliant
Up to 32 users
Up to 6 simultaneous views
Power supply: 12V DC (± 25%)
Consumption: 5W
Supports PoE (802.3 af, Class 3)
PoE consumption: 6.5W
-30 ° C ~ + 60 ° C operating temperature
Humidity: <95% (non-condensing)
Degree of protection IP67
Metal and plastic housing
Dimensions: Ø110 x 85.3 mm
Weight: 320g
3AXIS: 0 ° ~ 360 ° (PAN), 0 ° ~ 75 ° (TILT), 0 ° ~ 360 ° (Rotation)