

HYU-914

HYU-914

HYUNDAI

HYUNDAI NEXT GEN 1080P SMART IR 30M IP DOME IP67



- HYUNDAI Next Gen IP fixed dome with Smart IR 30m for outdoor use
- 1/2.8" 2MP CMOS
- Triple Stream
- H.265+, H.265, H.264+, H.264 and MJPEG compression formats
- Resolution up to 1080P at 25ips
- ICR filter
- 0.005 lux F1.6
- 2.8 mm (107°) fixed optics
- OSD, AWB, AGC, BLC, WDR 120dB, 3D-DNR, ROI, video sensor and privacy masks
- IVS intelligence
- Face detection
- Onvif (S/G), ISAPI
- IP67
- 3AXIS
- 12V DC
- Supports PoE



Reference / Model	HYU-914 / HYU-914
1/2.8" 2 megapixel CMOS image sensor	
Resolution: 1080P (1920x1080), 720P (1280x720), VGA (640x480)	
H.265+, H.265, H.264+, H.264, and MJPEG video compression	
Stream 1: 1080P, 720P (25 fps)	
Stream 2: VGA (25 fps)	
Stream 3: 720P, VGA (25 fps)	
Day/Night mode with removable mechanical filter (ICR)	
0.005 lux F1.6 (colour), 0 lux IR On	
Smart IR: 30 meters	
2.8 mm fixed optics	
Angle of view: 107°(H), 57°(V), 127°(D)	
Imaging modes: BLC, HLC, WDR 120dB, 3D-DNR	

HYUNDAI NEXT GEN 1080P SMART IR 30M IP DOME IP67

Reference / Model	HYU-914 / HYU-914
	Picture settings: Rotation, mirror, privacy mask, saturation, brightness, contrast, sharpness, gain, and white balance adjustable via client software or web browser
	Supports videosensor, 1 region of interest (ROI) per stream and privacy mask
	Cross-line detection and intrusion detection
	Face detection
	MicroSD card slot for up to 256GB (card not included)
	Network interface: RJ45 (10/100M) auto adaptive
	Network Protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour, SSL/TLS, PPPoE
	Remote viewing with browsers (IE10/11, Chrome 57.0+, Firefox 52.0+) and IOS and Android smartphones
	ONVIF (Profile S/G), ISAPI and SDK support
	DDNS support
	Up to 32 users
	Up to 6 simultaneous displays
	Power supply: 12V DC (±25%)
	Power consumption: 5W, 6.5W PoE
	Supports PoE (802.3 af, Class 3)
	Operating temperature -30°C ~ +60°C
	Humidity: <95% (non-condensing)
	IP67 protection rating
	Metal and plastic case
	Dimensions: Ø110.8 x 84.7 mm
	Weight: 530 g
	3AXIS: 0°~355°(PAN), 0°~75°(TILT), 0°~355°(Rotation)