

HYU-1034

SF-IPB180UWH-4U-WIDE

HYUNDAI

4MP wide-angle outdoor IP camera

4MP Professional Line IP67 WDR 120 dB H.265+    

- HYUNDAI Professional Line IP Camera
- 4MP@25ips, H.265+/H.265
- ICR, 0.028 lux, Smart IR 20m
- 1.68 mm optics
- WDR 120dB, 3D-DNR, ROI
- Perimeter protection and face detection
- MicroSD slot, RJ45, IP67, 3AXIS, 12V/PoE.



Reference / Model

HYU-1034 / SF-IPB180UWH-4U-WIDE

4 Megapixel 1/2.7" CMOS image sensor

Resolution: 4MP (2688x1520), 3MP (2304x1296), 1080P (1920x1080), 720P (1280x720), VGA (640x480), Q720P (640x360), QVGA (320x240)

H.265+, H.265, H.264+, H.264 and MJPEG video compression

Stream 1: 4MP, 3MP, 1080P, 720P (25/24 fps)

Stream 2: VGA, Q720P, QVGA (25/30 fps)

Day night mode with removable mechanical filter (ICR)

0.028 lux F2.0 (colour), 0 lux IR On

Smart IR: 20 meters

1.68 mm fixed optics

Viewing angle: 180°(H), 101°(V), 180°(D)

Imaging modes: BLC, HLC, EIS, lens correction, WDR 120dB, 3D-DNR

4 privacy masks

4MP wide-angle outdoor IP camera

Reference / Model	HYU-1034 / SF-IPB180UWH-4U-WIDE
1 fixed ROI zone for main stream and sub stream	
Saturation, brightness, contrast, sharpness, image rotation, gain and white balance adjustable via client software or web browser	
Perimeter protection: Cross-line detection, intrusion detection, intrusion detection	
Unattended baggage detection, removed object detection	
Face detection	
MicroSD card slot for up to 256GB (card not included)	
Network interface: RJ45 (10/100M) auto-adaptive	
Network protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, Websocket	
Onvif (S/G), ISAPI, SDK support	
Up to 32 users and 6 remote views	
Compatible with IE, Chrome and Firefox browsers	
Plug&Play connection with NVR NEXTGEN	
Compatible with DDNS DEMES	
Power supply: 12V DC ($\pm 25\%$) / PoE (802.3af)	
Power consumption: 7.2W (12V) / 8.7W (PoE)	
Operating temperature range: $-30^{\circ}\text{C} \sim +60^{\circ}\text{C}$	
Humidity: $<95\%$ (non-condensing)	
IP67 protection rating	
Metal housing	
Dimensions: $\varnothing 105 \times 278 \text{ mm}$	
Weight: 570 g	
3AXIS: $0^{\circ} \sim 355^{\circ}$ (PAN), $0^{\circ} \sim 90^{\circ}$ (TILT), $0^{\circ} \sim 360^{\circ}$ (ROTATION)	