

HYU-969

SF-IPD825ZWA-8P-HV

HYUNDAI

IP dome HYUNDAI 8MP outdoor



Professional Line



H.265+



- HYUNDAI IP dome
- 8MP@20ips, H.265+/H.265
- ICR, 0.005 lux, IR 40m
- Motorized optics 2.8~12 mm
- WDR 120dB, 3D-DNR, ROI
- Perimeter protection and facial detection
- Motion detection 2.0
- 1 input / 1 audio output
- 1 input / 1 alarm output
- MicroSD slot, Onvif, RJ45, IP67, IK10, 3AXIS, 12V/PoE



Reference / Model

HYU-969 / SF-IPD825ZWA-8P-HV

1/2.8" 8-megapixel CMOS image sensor

Resolution: 8MP (3840x2160), 6MP (3200x1800), 4MP (2688x1520), 1080P (1920x1080), 720P (1280x720), VGA (640x480), Q720P (640x360)

Video compression H.265+, H.265, H.264+, H.264 and MJPEG

Stream 1: 8MP (20fps), 6MP, 4MP, 1080P, 720P (25fps)

Stream 2: VGA, Q720P (25fps)

Stream 3: 1080P, 720P, VGA, Q720P (10fps)

Day/night mode with removable mechanical filter (ICR)

0.005 lux F1.6 (color, AGC On), 0 lux IR On

IR illumination: 40 meters

2.8~12mm motorized optics

View Angle: 108°~30°(H), 56°~17°(V), 131°~35°(D)

Image modes: BLC, HLC, WDR 120dB, 3D-DNR

IP dome HYUNDAI 8MP outdoor

| Reference / Model | HYU-969 / SF-IPD825ZWA-8P-HV |
|---|------------------------------|
| 1 fixed ROI zone for main and secondary streams | |
| Image rotation, mirroring, privacy masks, saturation, brightness, contrast, sharpness, white balance and gain control adjustable via client software or web browser | |
| Perimeter protection: Line crossing detection and intrusion detection with classification of people and vehicles | |
| Face detection | |
| Motion detection 2.0: Deep learning-based motion detection 2.0 is enabled by default for all analogue channels, can classify people and vehicles and minimise false alarms caused by lights or objects such as leaves | |
| 1 input / 1 audio output | |
| 1 input / 1 alarm output | |
| MicroSD card slot up to 256GB (card not included) | |
| Network interface: RJ45 (10/100M) self-adaptive | |
| Network Protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP | |
| Compliant with ONVIF (S/G), ISAPI, SDK | |
| Up to 32 users and 6 simultaneous views | |
| Compatible with IE, Chrome and Firefox browsers | |
| Plug&Play connection with NEXTGEN NVR | |
| Compatible with DDNS DEMES | |
| Power: 12V DC ($\pm 25\%$) / PoE (802.3af) | |
| Consumption: 10.5W (12V) / 12.5W (PoE) | |
| Operating temperature -30°C ~ +60°C | |
| Humidity: <95% (non-condensing) | |
| Degree of protection IP67 | |
| Vandal protection IK10 | |
| Metal casing | |
| Dimensions: Ø153.3 x 111.6mm | |
| Weight: 855g | |

HYU-969

SF-IPD825ZWA-8P-HV

HYUNDAI

IP dome HYUNDAI 8MP outdoor

Reference / Model

HYU-969 / SF-IPD825ZWA-8P-HV

3AXIS: 0°~355°(PAN), 0°~75°(TILT), 0°~355°(Rotation)
