

HYU-957

SF-IPD835WA-4P-HV

HYUNDAI

IP dome HYUNDAI 4MP outdoor



- HYUNDAI IP dome
- 4MP@25ips, H.265+/H.265
- ICR, 0.005 lux, IR 30m
- 2.8mm fixed lens
- WDR 120dB, 3D-DNR, ROI
- Perimeter protection and facial detection
- Motion detection 2.0
- 1 input / 1 audio output
- MicroSD slot, Onvif, RJ45, IP67, 3AXIS, 12V/PoE



Reference / Model	HYU-957 / SF-IPD835WA-4P-HV
1/3" 4 megapixel CMOS image sensor	
Resolution: 4MP (2688x1520), 1080P (1920x1080), 720P (1280x720), VGA (640x480), Q720P (640x360)	
Video compression H.265+, H.265, H.264+, H.264 and MJPEG	
Stream 1: 4MP, 1080P, 720P (25fps)	
Stream 2: VGA, Q720P (25fps)	
Stream 3: 1080P, 720P, VGA, Q720P (25fps)	
Day/night mode with removable mechanical filter (ICR)	
0.005 lux F1.6 (color, AGC On), 0 lux IR On	
IR illumination: 30 meters	
2.8mm fixed lens	
View Angle: 103°(H), 55°(V), 122°(D)	
Image modes: BLC, HLC, WDR 120dB, 3D-DNR	
1 fixed ROI zone for main and secondary streams	

IP dome HYUNDAI 4MP outdoor

Reference / Model	HYU-957 / SF-IPD835WA-4P-HV
	Image rotation, mirroring, privacy masking, saturation, brightness, contrast, sharpness, white balance and gain control adjustable via client software or web browser
	Perimeter protection: Line crossing detection and intrusion detection with classification of people and vehicles
	Face detection
	Motion detection 2.0: Deep learning-based motion detection 2.0 is enabled by default for all analogue channels, can classify people and vehicles and minimise false alarms caused by lights or objects such as leaves
	1 input / 1 audio output
	MicroSD card slot up to 256GB (card not included)
	Network interface: RJ45 (10/100M) self-adaptive
	Network Protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour, SSL/TLS, PPPoE
	Compliant with ONVIF (S/G), ISAPI, SDK
	Up to 32 users and 6 simultaneous views
	Compatible with IE, Chrome and Firefox browsers
	Plug&Play connection with NEXTGEN NVR
	Compatible with DDNS DEMES
	Power: 12V DC ($\pm 25\%$) / PoE (802.3af)
	Consumption: 5W (12V) / 6.5W (PoE)
	Operating temperature -30°C ~ +60°C
	Humidity: <95% (non-condensing)
	Degree of protection IP67
	Aluminum casing
	Dimensions: Ø110.8 x 84.7mm
	Weight: 530g
	3AXIS: 0°~355°(PAN), 0°~75°(TILT), 0°~355°(Rotation)