

HYU-945

SF-IPSD6625ITA-2P

HYUNDAI

PTZ Dome IP HYUNDAI 2MP, Zoom 25X, IR 50m, IP66

EMP Professional Line IP66 **STARLIGHT** 120 dB WDR **H.265+**   

- HYUNDAI IP PTZ dome
- 2MP@25fps, H.265+/H.264+
- ICR, 0.005/0.001 lux, IR 50m
- 25X optical zoom: 4.8~120mm
- BLC, HLC, WDR 120dB, 3D-DNR, Defog
- Pan&Tilt: 360°@300°/s (H); 90°@160°/s(V); 300 presets
- Two-way audio
- 2 inputs / 2 alarm outputs
- MicroSD slot, RJ45, Onvif, IP66, PoE+



Reference / Model

HYU-945 / SF-IPSD6625ITA-2P

specs

PTZ Dome IP HYUNDAI 2MP, Zoom 25X, IR 50m, IP66**Reference / Model****HYU-945 / SF-IPSD6625ITA-2P**

1/2.8" 2 Megapixel CMOS Image Sensor
Resolution: 1080P (1920x1080), 1.3MP (1280x960), 720P (1280x720), D1 (704x576), VGA (640x480), CIF (352x288)
Video compression H.265+, H.265, H.264+, H.264 and MJPEG
Stream 1: 1080P, 1.3MP, 720P (25fps)
Stream 2: D1, VGA, CIF (25fps)
Stream 3: 1080P, 1.3MP, 720P, D1, VGA, CIF (25fps)
Day/night mode with removable mechanical filter (ICR)
0.005 lux F1.6 (color), 0.001 lux F1.6 (B/W), 0 lux IR On
IR illumination: up to 50 meters
25X optical zoom: 4.8 ~ 120mm
View Angle: 54.9°~2.7°(H), 31.5°~1.5°(V), 62.3°~3.1°(D)
3.4 second zoom speed
Auto, semi-auto and manual focus mode
16X digital zoom
Image modes: BLC, HLC, WDR 120dB, 3D-DNR, Digital Defog
Regional exposure, regional focus
Supports video sensor, 8 regions of interest (ROI) in each stream and 24 programmable privacy masks
Brightness, saturation, contrast, sharpness, gain and white balance adjustments from client software and web browser
Horizontal positioner: 0° ~ 360°
Vertical positioner: -5° ~ 90°
Manual speed: 0.1° ~ 300°/sec. (H), 0.1° ~ 160°/sec. (V)
Preset speed: 350°/sec. (H), 200°/sec. (V)
300 presets, proportional zoom, 3D positioning
4 scan patterns, 8 rounds (32 presets per round)
1 input / 1 audio output
2 alarm inputs / 2 outputs
Slot for MicroSD/SDHC/SDXC up to 256GB (cards not included)
Self-adaptive RJ45 (10/100M) Ethernet network port
Network protocols: IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE, Bonjour
Compatible with IOS/Android browsers and phones
Compliant with ONVIF 18.12 (S/G/T), ISAPI, SDK and ISUP
Up to 32 users
Up to 20 simultaneous views
Power: 12V DC / PoE+ (802.3at)
Consumption: Maximum 18W
Operating temperature -30°C ~ +65°C
Operating humidity up to 90% (non-condensing)
Degree of protection IP66
Dimensions: Ø169 x 161mm
Weight: 2.45kg
Includes feeder