

HYU-913

SF-IPB798ZWA-4P-HV

HYUNDAI

HYUNDAI NEXT GEN IP CAMERA 4MP SMART IR 60M IP67



- HYUNDAI Next Gen IP bullet camera with 60m Smart IR for outdoor use
- 1/3" 4MP CMOS
- Triple Stream
- H.265+, H.265, H.264+, H.264 and MJPEG compression formats
- Resolution up to 4MP at 25ips
- ICR filter
- 0.005lux F1.6
- 2.8~12mm motorized optics (95.8°~29.8°)
- OSD, AWB, AGC, BLC, WDR 120dB, 3D-DNR, ROI, video sensor and privacy masks
- IVS intelligence
- Face detection
- Two-way audio
- 1 input / 1 alarm output
- Onvif (S/G), ISAPI
- IP67
- 3AXIS
- 12V DC
- PoE+ supported



Reference / Model	HYU-913 / SF-IPB798ZWA-4P-HV
4 megapixel 1/3" CMOS image sensor	
Resolution: 4MP (2688x1520), 1080P (1920x1080), 720P (1280x720), VGA (640x480)	
H.265+, H.265, H.264+, H.264 and MJPEG video compression	
Stream 1: 4MP, 1080P, 720P (25 fps)	
Stream 2: VGA (25 fps)	
Stream 3: 720P, VGA (25 fps)	
Day/Night mode with removable mechanical filter (ICR)	
0.005 lux F1.6 (color), 0 lux IR On	
Smart IR: 60 meters	
2.8 ~ 12 mm motorized optics	
Angle of view: 95.8°~29.8°(H), 50.6°~16.4°(V), 114.6°~33.4°(D)	

HYUNDAI NEXT GEN IP CAMERA 4MP SMART IR 60M IP67

Reference / Model	HYU-913 / SF-IPB798ZWA-4P-HV
Picture modes: BLC, HLC, WDR 120dB, 3D-DNR.	
Image settings: Rotation, mirror, privacy mask, saturation, brightness, contrast, sharpness, gain, and white balance adjustable via client software or web browser	
Supports videosensor, 1 region of interest (ROI) per stream and privacy mask	
Cross-line detection and intrusion detection	
Face detection	
MicroSD card slot for up to 256GB (card not included)	
Two-way audio	
1 alarm input / 1 alarm output	
Network interface: RJ45 (10/100M) self-adapting	
Network protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour, SSL/TLS, PPPoE	
Remote viewing with browsers (IE10/11, Chrome 57.0+, Firefox 52.0+) and IOS and Android smartphones	
ONVIF (Profile S/G), ISAPI and SDK support	
DDNS support	
Up to 32 users	
Up to 6 simultaneous displays	
Power supply: 12V DC ($\pm 25\%$)	
Power consumption: 13W, 15W PoE	
Supports PoE+ (802.3 at, Class 4)	
Operating temperature from $-30^{\circ}\text{C} \sim +60^{\circ}\text{C}$	
Humidity: $<95\%$ (non-condensing)	
IP67 protection rating	
Aluminum housing	
Dimensions: 97.9 (W) x 93.1 (H) x 312.1 mm (W) x 93.1 (H) x 312.1 mm (H)	
Weight: 1.4 kg	
3AXIS: $0^{\circ} \sim 360^{\circ}$ (PAN), $0^{\circ} \sim 90^{\circ}$ (TILT), $0^{\circ} \sim 360^{\circ}$ (Rotation)	