

HYU-955

HYU-955

HYUNDAI

HYUNDAI Solar WiFi IP Camera with 4G



- HYUNDAI ColorView Solar WiFi IP Camera with 4G
- 4MP@12ips, H.265+/H.265
- ICR, 0.0005 lux, white light 30m
- 4mm fixed lens
- WDR 120dB, 3D-DNR, ROI
- Two-way audio with microphone and speaker
- MicroSD slot, incorporates 64GB eMMC, RJ45, IP67
- Autonomous with solar panel and battery



Reference / Model

HYU-955 / HYU-955

specs

HYUNDAI Solar WiFi IP Camera with 4G**Reference / Model****HYU-955 / HYU-955**

1/1.8" 4 Megapixel CMOS Image Sensor
Resolution: 4MP (2688x1520), 1080P (1920x1080), 720P (1280x720), VGA (640x480), Q720P (640x360)
Video compression H.265+, H.265, H.264+, H.264 and MJPEG
Stream 1: 4MP, 1080P, 720P (12fps)
Stream 2: VGA, Q720P (12fps)
24h color mode
0.0005 lux F1.0 (color, AGC On), 0 lux white led on
White lighting: up to 30 meters
4mm fixed lens
View Angle: 95°(H), 51°(V), 115°(D)
Image modes: BLC, HLC, WDR 120dB, 3D-DNR
1 fixed ROI zone in main stream
Rotation, saturation, brightness, contrast, sharpness, white balance and gain control adjustment via client software or web browser
PIR motion sensor with up to 15 meters range. 100° horizontal and 80° vertical
Two-way audio: incorporates microphone and speaker
It incorporates 64GB of eMMC storage with 50GB available for recording
MicroSD card slot up to 256GB (card not included)
Network interface: RJ45 (10/100M) self-adaptive
Network Protocols: TCP/IP, ICMP, HTTP, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, QoS, IPv6, UDP, Bonjour, SSL/TLS, SNMP, HTTPS, 802.1X
Compliant with ONVIF, ISAPI, SDK, ISUP
Up to 32 users and 6 simultaneous views
Compatible with IE, Chrome and Firefox browsers
Plug&Play connection with NEXTGEN NVR
Compatible with DDNS DEMES
4G LTE mobile communication
Autonomous operation with built-in solar panel and battery
Ø5.5mm coaxial power interface
Extended Solar Panel: Quad Core Aviation Connector
Power: 12V DC (±25%)
Consumption: 1.85W (4G) / 40mW (autonomous scenario) / 7.2W (maximum)
Operating temperature -20°C ~ +50°C
Humidity: <95% (non-condensing)
Degree of protection IP67
Dimensions: 760 (W) x 614 (H) x 390.5 mm
Weight: 11.8kg