

HYU-1081

SF-NVR6104-4KE-4P / SF-NVR6104-4KE

HYUNDAI

4-channel IP NVR with PoE



- HYUNDAI NEXTGEN 4-channel IP NVR
- H.265+/H.265/H.264+/H.264
- 4-channel synchronized playback
- Up to 8MP display
- Recording 8MP, 6MP, 5MP, 4MP, 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc
- Recording up to 40 Mbps
- HDMI 4K and VGA 1080P output
- Bidirectional audio
- Motion detection 2.0
- Supports 1 SATA HDD
- RJ45 Fast Ethernet
- 48V DC / 4 PoE+



Reference / Model	HYU-1081 / SF-NVR6104-4KE-4P / SF-NVR6104-4KE
4 IP channels	
Video compression: H.265+, H.265, H.264+, H.264	
HDMI (4K) and VGA (1080P) video output simultaneously	
1 RCA input / 1 RCA audio output	
Bi-directional audio via RCA input/output	
Recording resolution: 8MP, 6MP, 5MP, 4MP, 4MP, 3MP, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF	
Incoming bandwidth: 40 Mbps	
Outgoing bandwidth: 80 Mbps	
Decoding capacity: 1 channel at 8MP (30 fps), 3 channels at 4MP (30 fps), 6 channels at 1080P (30 fps)	
4-channel synchronized playback	
Internal capacity for 1 SATA HDD up to 8TB (sold separately)	
Support 1 channel of Motion Detection 2.0	
Configurable special camera intelligent functions, such as motion detection, line crossing, intrusion	

4-channel IP NVR with PoE

Reference / Model	HYU-1081 / SF-NVR6104-4KE-4P / SF-NVR6104-4KE
	Supports VCA (video content analysis) events
	Support intelligent search
	RJ45 Fast Ethernet (10/100Mbps) network port
	4 PoE ports (IEEE802.3af/at) with an output power of 25.5W per port and a total of 50W
	Network protocols: TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS
	Up to 32 remote connections
	Remote access via iPhone/iPad, Android devices
	Multi-browser support: Chrome, Firefox, Safari, IE
	P2P in the cloud, DDNS DEMES, Push and zero channel
	Plug&Play connection with NEXTGEN IP cameras
	Communication ports: 2 USB 2.0 ports
	Power supply: 48V DC, 1.35A
	Consumption: ≤10W (excluding disks and with PoE disabled)
	Operating temperature from -10°C ~ +55°C
	Relative humidity 10% ~ 90%
	Dimensions: 320 (W) x 48 (H) x 240 mm
	Weight: ≤1.18 kg
	Desktop installation