

HYU-689N

HYU-689N

HYUNDAI

DOMO PTZ 4-IN-1, 80°/S, 2MP, ZOOM 15X, SMART IR 100M, IP66



- 4-in-1 motorized dome of 80 ° / sec
- with IR illumination of 100 m, for outdoors
- 2 megapixel 1 / 2.8 "CMOS
- 1080P 25 ips resolution
- 5 ~ 75mm 15X optical zoom (53.8 ° ~ 4 °)
- 16X digital zoom
- 4-in-1 output (HDCVI / HDTVI / AHD / CVBS)
- ICR filter
- OSD, AWB, AGC, BLC, HLC, EIS, WDR 120 dB, 3D-DNR
- 8 privacy masks
- 256 presets
- Pelco-D / P
- RS485 Half Duplex
- IP66, Lightning-proof 12V DC includes wall bracket
Does not include power supply



Reference / Model

HYU-689N / HYU-689N

specs

DOMO PTZ 4-IN-1, 80°/S, 2MP, ZOOM 15X, SMART IR 100M, IP66**Reference / Model****HYU-689N / HYU-689N**

1 / 2.8 "CMOS sensor, 2 megapixel
Digital Resolution: 1080P (1920x1080)
Day / night mode with removable mechanical filter
Infrared illumination up to 100 meters
0.005 lux F1.6 color / 0.001 lux F1.6 B / W / 0 lux IR On
15X optical zoom: 5 ~ 75mm
Viewing angle: 53.8 ° ~ 4 ° (H)
Automatic, semi-automatic and manual focus modes
2.4 second zoom speed
16X digital zoom
4 in 1 output: HDCVI / HDTV / AHD / CVBS
Imaging Modes: BLC, HLC, WDR 120dB, 3D-DNR, EIS, Regional Focus
Automatic and manual gain control
White balance with 6 modes
8 programmable privacy masks
Horizontal positioner: 360 ° continuous
Vertical positioner: -15 ° ~ 90 °, autoflip 180 °
Manual speed: 0.1 ° ~ 80 ° / sec. (H), 0.1 ° ~ 80 ° / sec. (V)
Preset speed: 80 ° / sec. (H), 80 ° / sec. (V)
256 presets
Pelco-D / P protocols (RS485 half-duplex), HYUNDAI protocol
5 patterns (with a total recording of not less than 10 minutes), 10 rounds (32 presets per round)
RS485 half-duplex interface
Power supply: 12V DC, max. 20W (IR 7W)
-30 ° C ~ + 65 ° C operating temperature
Humidity: <90%
Degree of protection IP66
Lightning-proof (4000V), surge and surge protection
Dimensions: Ø164.5 x 295 mm
Weight: 2 kg
Includes wall bracket
Does not include feeder