

HIK-415N

HWP-N2404IH-DE3(F)

HIKVISION
HiWatch Series

HIKVISION 4MP 4X outdoor PTZ IP dome



- HIKVISION HiWatch IP PTZ dome
- 4MP@25fps, H.265+/H.265
- ICR, 0.005/0.001 lux, Smart IR 20m
- 4X optical zoom: 2.8~12mm
- WDR 120dB, 3D-DNR
- IVS intelligence
- Pan&Tilt: 355°@100°/s (H); 90°@100°/s(V); 300 presets
- MicroSD slot, RJ45, Onvif, IP66, IK10, 12V DC, PoE



Reference / Model

HIK-415N / HWP-N2404IH-DE3(F)

specs

HIKVISION 4MP 4X outdoor PTZ IP dome**Reference / Model****HIK-415N / HWP-N2404IH-DE3(F)**

1/2.8" 4 Megapixel CMOS Image Sensor
Resolution: 4MP (2560x1440), 1080P (1920x1080), 1.3MP (1280x960), 720P (1280x720), D1 (704x576), VGA (640x480), CIF (352x288)
Video compression H.265+, H.265, H.264+, H.264 and MJPEG
Stream 1: 4MP, 1080P, 1.3MP, 720P (25fps)
Stream 2: D1, VGA, CIF (25fps)
Stream 3: D1, VGA, CIF (25fps)
Day/night mode with removable mechanical filter (ICR)
0.005 lux F1.5 (color), 0.001 lux F1.5 (B/W), 0 lux IR On
Smart IR: 20 meters
4X optical zoom: 2.8 ~ 12mm
View Angle: 100°~33°(H), 53°~18°(V), 119°~37.5°(D)
2 second zoom speed
Auto, semi-auto and manual focus mode
16X digital zoom
Image modes: BLC, HLC, WDR 120dB, 3D-DNR
Regional exposure, regional focus
White balance with 7 modes
Automatic and manual gain control
Supports video sensor, 2 regions of interest (ROI) in each stream and 24 programmable privacy masks
Intelligent Detection: Intrusion, Line Crossing, Area Entry Detection, Area Exit Detection, Object Removal Detection, Unattended Baggage Detection, Audio Exception Detection
face detection
1 input / 1 audio output
Horizontal positioner: 0°~355°
Vertical positioner: 0° ~ 90°
Manual speed: 0.1° ~ 100°/sec. (H), 0.1° ~ 100°/sec. (V)
Preset speed: 100°/sec. (H), 100°/sec. (V)
Supports proportional zoom
300 presets
Slot for MicroSD/SDHC/SDXC up to 256GB (cards not included)
Self-adaptive RJ45 (10/100M) Ethernet network port
Network Protocols: IPv4/IPv6, HTTP, HTTPS, 802.1x, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE, Bonjour
Compatible with IE10-11, Chrome 57+, Firefox 52+ and Safari 11`+ browsers
Compatible with ONVIF, ISAPI, Hikvision SDK and CGI
Compatible with iVMS-4200, HikCentral Pro and Hik-Connect software
Up to 32 users
Up to 20 simultaneous views
Power: 12V DC (1.5A) / PoE (802.3af)
Consumption: 9.9W (12V) / 11.2W (PoE)
Operating temperature -20°C ~ +60°C
Operating humidity of ≤90% (non-condensing)
Degree of protection IP66
Vandal protection IK10
aluminum casing
Dimensions: Ø130.7 x 101.7mm
Weight: 530g