

HYU-942

SF-IPPT111HA-2E-W

HYUNDAI

WiFi IP camera 2MP IR 10m for interior



- HYUNDAI Wi-Fi IP camera
- 2MP@25ips, H.265+/H.265
- ICR, 0.028 lux, IR 10m
- 2.8mm fixed lens
- Digital WDR, 3D-DNR
- Microphone and speaker
- MicroSD slot
- Not suitable for outdoor use, 2AXIS, 5V DC



Reference / Model

HYU-942 / SF-IPPT111HA-2E-W

specs

WiFi IP camera 2MP IR 10m for interior**Reference / Model****HYU-942 / SF-IPPT111HA-2E-W**

1/2.7" 2 Megapixel CMOS Image Sensor
Resolution: 1080P (1920x1080), 720P (1280x720), Q720P (640x360)
Video compression H.265+, H.265, H.264+, H.264 and MJPEG
Stream 1: 1080P, 720P (25fps)
Stream 2: Q720P (25fps)
Day/night mode with removable mechanical filter (ICR)
0.028 lux F2.0 (color, AGC On), 0 lux IR On
IR illumination: 10 meters
2.8mm fixed lens
View Angle: 112°(H), 60°(V), 132°(D)
Picture modes: BLC, HLC, digital WDR, 3D-DNR
Brightness, saturation, contrast, sharpness, gain control and white balance adjustment via client software
Includes microphone and speaker
MicroSD card slot up to 256GB (card not included)
Network interface: RJ45 (10/100M) self-adaptive
Network protocols: TCP/IP, ICMP, DHCP, DNS, DDNS, HTTP, RTP, RTSP, NTP, UPnP, IGMP, IPv6, UDP, QoS, Bonjour
WiFi: IEEE802.11b/g/n, 2.4GHz (up to 80 meters in open field)
ISAPI and SDK Compliant
Up to 32 users and 6 simultaneous views
Plug&Play connection with NEXTGEN NVR
Compatible with DDNS DEMES
Power supply: 5V DC (±10%) via micro USB interface
Consumption: 1.6A, 8W max.
Operating temperature -10°C ~ +40°C
Humidity: <95% (non-condensing)
Not suitable for outdoors
Plastic shell
Dimensions: Ø82.4 x 113.6mm
Weight: 280g
2AXIS: 0°~355°(PAN), -10°~90°(TILT)