

HYU-1045

SF-VIK001-F-IP

HYUNDAI

HYUNDAI video door entry kit



- HYUNDAI IP video door entry system kit consisting of:
- 1x IP video door entry system
- 1x IP WiFi monitor
- 1x 4-port PoE switch
- 1x 16GB TF card



Reference / Model

HYU-1045 / SF-VIK001-F-IP

HYUNDAI IP video door station suitable for outdoor use

1 call button

2 MP fisheye camera with 146°(H)/82°(V) viewing angle

H.264 video format

Infrared night vision

WDR backlight

Built-in microphone and speaker

Noise suppression and echo cancellation

Adjustable volume

Tamper tamper

Up to 2000 users

Up to 6000 cards

Connection of up to 500 indoor monitors

HYUNDAI video door entry kit**Reference / Model****HYU-1045 / SF-VIK001-F-IP**

Sub-connection of up to 16 video door phones

4 alarm inputs (2 exit buttons and 2 door contacts by default)

Supports 2 exit request buttons (for door lock)

2 door contact inputs

2 door lock control ports

1 RS485 port for submodules

1 RJ45 port (10/100 Mbps)

TCP/IP, RTSP protocols

1 power output 12V DC, 500 mA

Power supply: 12V DC / PoE (802.3af)

Power consumption: $\leq 5W$

Operating temperature from $-40^{\circ}C \sim +60^{\circ}C$

Operating relative humidity 10% ~ 95% (non-condensing)

IP65 degree of protection

Dimensions: 98 (W) x 100 (H) x 42 mm

In-ceiling installation

1x WIFI IP monitor

7" TFT capacitive touch screen (1024x600)

Stores messages and captures images on 16GB TF card (included)

Remote unlock via client software or mobile client

View live video from video door phones and linked cameras

Built-in microphone and speaker

G.711u audio compression

Noise suppression and echo cancellation

Adjustable volume

200 event logging

HYUNDAI video door entry kit**Reference / Model****HYU-1045 / SF-VIK001-F-IP**

Capacity for up to 16 notifications

Capacity for up to 5 connected indoor extensions

Capacity for up to 8 connected video door stations

8 alarm inputs / 2 alarm outputs

1 RS485 port

1 RJ45 port (10/100Mbps)

Protocols TCP/IP, SIP, RTSP

Built-in WiFi 802.11 b/g/n

1 power port

Power consumption: $\leq 6W$ Operating temperature from $-10^{\circ}C \sim +55^{\circ}C$

Operating relative humidity 10% ~ 90% (non-condensing)

Indoor installation environment

Dimensions: 200 (W) x 140 (H) x 23,6 mm

Weight: 355 g

Surface mounting