

HYU-1049

SF-VIK001-S-2

HYUNDAI

2-wire video door entry kit



- 2-wire video door entry kit
- Plug&Play, easy and cost-effective
- Receives video calls and unlocks through the indoor station
- 7" capacitive TFT touch screen with 1024x600 resolution and WiFi
- 2MP HD colour camera
- Colour display, even in the dark
- One-touch call with name tag
- IP65 waterproof
- 2 lock relays
- 2-wire to IP converter with 6 status indicators.



Reference / Model

HYU-1049 / SF-VIK001-S-2

HYUNDAI video door station suitable for outdoor use

1x call button

2 megapixel HD camera with IR light supplement

Viewing angle 146°(H), 82°(V)

Wide dynamic range WDR real WDR, BLC, DNR

Video format H.264

Resolution: 1080P (1920x1080), 720P (1280x720)

Stream 1: 1080P, 720P (30 fps)

Stream 2: D1 (30 fps)

Motion sensor

Bi-directional audio with omni-directional microphone and loudspeaker

G.711 U audio format

Noise suppression and echo cancellation

2-wire video door entry kit

Reference / Model	HYU-1049 / SF-VIK001-S-2
	Tamper tamper
	4 alarm inputs (2 output buttons and 2 default contacts)
	2 door lock control relays
	1 debug port
	RS485 port for sub-module connection
	Two-wire power interface
	Operating temperature: -40°C ~ +60°C
	Operating humidity: 10% ~ 90%
	IP65 degree of protection
	Dimensions: 100 (W) x 98 (H) x 42 mm
	Wall installation
	1x 2-wire WIFI monitor
	7" (1024x600) capacitive TFT colour touchscreen display
	Two-way audio with omni-directional microphone and loudspeaker
	Noise suppression and echo cancellation
	Local or software volume control
	G.711U and G.711A audio formats
	TF card slot up to 128GB (16GB card included)
	8 alarm inputs
	2 relay outputs
	RS485 interface
	Two-wire network interface
	Built-in WiFi 802.11 b/g/n
	TCP/IP, SIP, RTSP protocol
	Power supply via 2-wire to IP converter
	Power consumption: ≤4W

2-wire video door entry kit**Reference / Model****HYU-1049 / SF-VIK001-S-2**

Operating temperature: -10°C ~ +50°C

Operating Humidity: 10% ~ 90%

Indoor installation environment

Dimensions: 200 (W) x 140 (H) x 23.6 mm

Surface installation

1x 2-wire to IP converter

2-wire to IP converter

6 2-wire channels (2 hub channels for cascade + 4 device channels)

TCP/IP connection via RJ45

6 status indicators

1 power indicator

Power supply: 24V DC

Power consumption: <4W (channels 1 to 3), <8W (channel 4)

Operating Temperature: -10°C ~ +55°C

Surface or rail mounting