

HYU-1073

HYU-1073

HYUNDAI

HYUNDAI modular 2-wire video door entry system



- HYUNDAI 2-wire video door station
- 2MP camera with IR supplement and WDR
- 1 single or double call button (freely adjustable)
- Built-in microphone and speaker
- Up to 2000 users
- 2 alarm inputs
- Supports two lock control
- Supports mobile web configuration (AP mode)
- IP65 and IK08 protection
- 12V DC / 48V DC



Reference / Model

HYU-1073 / HYU-1073

Embedded Linux operating system

4GB ROM memory

256MB RAM memory

Embedded processor

Single- or double-button calling (freely adjustable)

2 megapixel camera with infrared supplement

Viewing angle: 133°(H), 82°(V)

H.264 video compression

Backlight compensation with WDR

Built-in omni-directional microphone and loudspeaker

G.711U and G.711A audio compression

Noise suppression and echo cancellation

Adjustable volume

HYUNDAI modular 2-wire video door entry system

Reference / Model	HYU-1073 / HYU-1073
	Capacity up to 2000 users
	Connection with up to 99 indoor monitors
	Connection with up to 16 sub-modules
	2 RS485 ports (for connection with sub-modules)
	Tamper tamper
	2 alarm inputs (supports request-to-exit button or door contact input)
	6 decimal DIP switch
	Door control: 2 (1 relay, 30V DC, 2A / 1 pulse DC, 20V, 4A pulse, 300 mA holding current, 30 ohm max)
	10/100 Mbps network port self-adaptable via 2-wire interface
	Power supply: external 12V DC or 48V power supply not included
	Power consumption: $\leq 6W$
	Operating temperature from $-40^{\circ}C \sim +60^{\circ}C$
	Operating humidity 10% ~ 90%
	IP65 degree of protection
	Vandal protection IK08
	Aluminum housing
	Surface or flush mounting
	Dimensions: 99,5 (W) x 98,5 (H) x 35 mm
	Net weight: 290 g
	Gross weight: 426 g