

HYU-973

SF-IPD821WHA-4PW

HYUNDAI

Outdoor 4MP WiFi IP Dome



- HYUNDAI Wi-Fi IP dome camera
- 4MP@20ips, H.265/H.264
- ICR, 0.005 lux, EXIR IR 30m
- 2.8mm lens
- WDR 120dB, 3D-DNR, image settings
- Built-in two way audio
- MicroSD slot, RJ45, IP66, 3AXIS



Reference / Model	HYU-973 / SF-IPD821WHA-4PW
1/2.7" 4 megapixel CMOS sensor	
Digital resolution: 4MP (2560x1440), 3MP (2304x1296), 1080P (1920x1080), 720P (1280x720), Q720P (640x360)	
H.265/H.264 compression format	
Main Stream: 4MP (20fps), 3MP, 1080P, 720P (25/30fps)	
Secondary stream: Q720P (25/30 ips)	
Day/night mode with removable mechanical filter	
Infrared illumination: EXIR 30 meters	
0.005 lux F1.6	
2.8mm fixed lens	
95°(H), 53°(V), 111°(D) viewing angle	
Image modes: BLC, HLC, WDR 120dB, 3D-DNR	
Adjust mirror mode, saturation, brightness, contrast, sharpness, gain control and white balance via client software and web browser	

Outdoor 4MP WiFi IP Dome

Reference / Model	HYU-973 / SF-IPD821WHA-4PW
Built-in two-way audio	
MicroSD/SDHC/SDXC card slot up to 256GB (card not included)	
Network interface: RJ45 (10/100M) self-adaptive	
Network protocols: TCP/IP, ICMP, DHCP, DNS, DDNS, HTTP, HTTPS, RTP, RTSP, NTP, UPnP, IGMP, IPv6, UDP, QoS, Bonjour	
Built-in WiFi 802.11b/g/n at 2.4GHz with WEP security, WPA-EAP/WPA2-EAP, WPA-PSK/WPA4-PSK	
WiFi range of up to 120 meters in open field without obstacles	
Compatible with ISAPI and SDK	
Up to 6 simultaneous displays	
Up to 32 remote users	
Plug&Play connection with NEXTGEN NVR	
Compatible with DDNS DEMES	
Power supply: 12V DC ($\pm 25\%$), max 7W	
Operating temperature $-30^{\circ}\text{C} \sim +60^{\circ}\text{C}$	
Humidity 95% or less (non-condensing)	
Degree of protection IP66	
Polycarbonate casing	
Dimensions: $\varnothing 126 \times 96,1 \text{ mm}$	
Weight: 590g	
3AXIS: $0^{\circ} \sim 355^{\circ}$ (PAN), $0^{\circ} \sim 75^{\circ}$ (TILT), $0^{\circ} \sim 355^{\circ}$ (Rotation)	