

HYU-1041

SF-NVR6116-4KE

HYUNDAI

16-channel IP NVR



- 16-channel IP NVR
- H.265+/H265 formats
- 160/80Mbps I/O
- VGA 1080P and HDMI 4K outputs
- Two-way audio
- Motion detection 2.0 on up to 4 channels
- Supports 1 SATA HDD
- RJ45 Gigabit
- 12V DC, 1U



Reference / Model	HYU-1041 / SF-NVR6116-4KE
16 IP camera inputs	
H.265+, H.265, H.264+ and H.264 compression format	
Incoming bandwidth: 160 Mbps	
Outgoing bandwidth: 80 Mbps	
Simultaneous VGA 1080P and HDMI 4K video outputs	
Bi-directional audio: 1 RCA input / 1 RCA output	
Recording resolution: 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF	
Decoding capability: 1 channel 8MP (30 fps), 3 channels 4MP (30 fps), 6 channels 1080P (30 fps)	
16-channel synchronised playback	
1 SATA port up to 8TB (HDD not included)	
Supports multiple VCA (Video Content Analytics) events from IP cameras	
Motion Detection 2.0 on up to 4 channels: Deep learning-based Motion Detection 2.0 can classify people and vehicles and minimise false alarms caused by lights or objects such as leaves.	

16-channel IP NVR

Reference / Model	HYU-1041 / SF-NVR6116-4KE
Intelligent search	
Auto-adaptive RJ45 Ethernet (10/100/1000M) network interface	
Network protocols: TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS	
Up to 32 remote connections	
Connections: 2 USB 2.0	
Power: 12V DC, 1.5A	
Power consumption: ≤10W (without HDD)	
Operating Temperature: -10°C ~ +55°C	
Relative humidity: 10~90%.	
Dimensions: 320 (W) x 48 (H) x 320 mm	
Weight: ≤1 kg	