HYUNDAI

SF-VIDISP01-7IP

HYUNDAI Indoor IP Monitor







- HYUNDAI indoor IP monitor
- 7" (1024x600) capacitive colour touch screen
- Built-in microphone and speaker
- Up to 200 events
- Fast Ethernet
- 8 alarm inputs
- SD slot
- Surface installation



	HYU-1043 / SF-VIDISP01-7IP
Embedded Linux operating system	
128MB RAM memory	
32MB ROM memory	
7" capacitive TFT touch screen (1024x600)	
Built-in omnidirectional microphone	
Built-in speaker	
G.711U audio compression	
Noise suppression and echo cancellation	
Adjustable volume	
Logging of up to 200 events	
Up to 16 notifications	
Ability to connect up to 5 indoor monitors	
Ability to connect up to 8 outdoor video door stations	

HYUNDAI Indoor IP Monitor

Reference / Model	HYU-1043 / SF-VIDISP01-7IP
Auto-adaptive RJ45 10/100Mbps network port	
Network protocol: TCP/IP, SIP, RTSP	
8 alarm inputs	
SD card slot for up to 128GB (card not included)	
Power consumption: ≤6W	
Operating Temperature: -10°C ~ +55°C	
Operating humidity: 10% ~ 90%	
Indoor installation environment	
Dimensions: 200 (W) x 140 (H) x 15.1 mm	
Weight: 350 g	
Surface installation	