

HYU-1115

HYU-1115

HYUNDAI

8-channel IP NVR with PoE



- HYUNDAI 8-channel IP NVR
- H.265+/H265 formats
- Up to 12MP recording
- 80/80Mbps input/output
- VGA 1080P and HDMI 4K outputs
- Two-way audio
- Facial recognition, motion detection 2.0
- Supports 1 SATA HDD
- 8 PoE+ ports



| Reference / Model | HYU-1115 / HYU-1115 |
|---|---------------------|
| 8 IP camera inputs | |
| H.265+, H.265, H.264+, H.264, H.264 compression format | |
| Incoming bandwidth: 80 Mbps | |
| Outgoing bandwidth: 80 Mbps | |
| Independent VGA 1080P and HDMI 4K video outputs | |
| Bidirectional audio: 1 RCA input / 1 RCA output | |
| Recording resolution: 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF | |
| Face recognition: 1 channel of face detection, 4 channels of face image comparison alarm | |
| Motion detection 2.0: 8 channels | |
| 8-channel synchronized playback | |
| Decoding capability: | |
| AI enabled: 1 channel 12MP @ 30 fps, 1 channel 8MP @ 30 fps, 3 channels 4MP @ 30 fps, 6 channels 1080P @ 30 fps | |
| AI off: 1 channel 12MP @ 30 fps, 2 channels 8MP @ 30 fps, 4 channels 4MP @ 30 fps, 8 channels 1080P @ 30 fps | |

8-channel IP NVR with PoE

| Reference / Model | HYU-1115 / HYU-1115 |
|-------------------|---|
| | Internal capacity for 1 SATA HDD up to 10TB (sold separately) |
| | Intelligent search of selected area in the video and intelligent playback to improve playback efficiency |
| | Video stream encryption technology over TLS |
| | Auto-adaptive RJ45 (10/100/1000M) Ethernet network interface |
| | Network protocols: TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS |
| | Up to 128 remote connections |
| | Communication ports: 2 USB 2.0 ports |
| | Rear panel incorporates 8 independent (100Mbps) PoE+ 802.3af/at ports |
| | PoE delivery: ≤75W |
| | Power supply: 48V DC, 1.875 A |
| | NVR Consumption: ≤10W (without hard drives and PoE consumption) |
| | Operating Temperature: -10°C ~ +55°C |
| | Relative humidity: 10 ~ 90% |
| | Dimensions: 320 (W) x 48 (H) x 240 mm |
| | Weight: ≤1 kg |