

# HYU-562N

SF-XVR8104AS-4KL-POC

HYUNDAI

## HYUNDAI 5-in-1 4-channel ZVR



- HYUNDAI 4-channel 5-in-1 ZVR
- H.265+/H.265 formats
- 4 BNC channels + 4 IP channels
- 8MP@8ips recording (1 channel)
- HDMI 2K and VGA 1080P outputs
- Bi-directional audio
- 4 inputs / 1 alarm output
- Supports 1 HDD 10TB, 1 RJ45, 1 RS485, 2 USB, Onvif
- PoC power supply to compatible cameras



### Reference / Model

**HYU-562N / SF-XVR8104AS-4KL-POC**

ZVR 5 in 1 with 4 HD analogue channels + 4 IP channels

5 technologies: IP, HDCVI, HDTVI, AHD and analogue CVBS cameras

H.265 Pro+, H.265 Pro, H.265, H.264+, H.264+, H.264 video formats

4 BNC inputs (supports coax):

HDCVI: 4MP, 1080P, 720P

HDTVI: 8MP, 5MP, 4MP, 3MP, 1080P, 720P

AHD: 5MP, 4MP, 1080P, 720P

CVBS analogue: 960H, PAL/NTSC

4 IP inputs (4+4), channel 1 up to 8MP

Independent HDMI (2K) and VGA (1080P) outputs

BNC video output

Audio channels: 4 RCA inputs / 1 RCA output

Bi-directional audio: via RCA audio channel 1

**HYUNDAI 5-in-1 4-channel ZVR**

<b>Reference / Model</b>	<b>HYU-562N / SF-XVR8104AS-4KL-POC</b>
	Recording resolution: 8MP, 5MP, 4MP, 3MP, 1080P, 720P, WD1, 4CIF, VGA, CIF
	Stream 1: 8MP (8 fps, 1 channel only), 5MP (12 fps), 4MP (15 fps), 3MP (18 fps), 1080P, 720P, WD1, 4CIF, VGA, CIF (25/30 fps)
	Stream 2: WD1, 4CIF, CIF (25/30 fps)
	4-channel synchronised playback
	Long distance HDTV transmission: up to 1200 metres at 720P and 800 metres at 1080P
	Internal capacity for 1 SATA HDD up to 10TB (sold separately)
	Intelligent Search
	Supports multiple VCA (Video Content Analytics) events for both analogue and smart IP cameras
	Supports cross-line detection and intrusion detection on all channels, as well as sudden scene change detection on 2 channels
	4 alarm inputs / 1 alarm output
	Auto-adaptive RJ45 (10/100M) Ethernet network interface
	Network protocols: TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS
	Remote access for up to 32 users
	Onvif compatible
	P2P in the cloud, DDNS DEMES, Push and zero channel
	Connections: 2 USB 2.0, 1 RS485 (half-duplex)
	Power supply: 48V DC, 1A
	Power consumption: ≤40W
	Supplies power to PoC cameras via coaxial cable
	Operating temperature: -10°C ~ +55°C
	Relative humidity: 10~90%.
	Dimensions: 315 (W) x 45 (H) x 242 mm (desktop)
	Weight: ≤1.5 kg

**HYUNDAI 5-in-1 4-channel ZVR****Reference / Model****HYU-562N / SF-XVR8104AS-4KL-POC**

ZVR 5 in 1 with 4 HD analogue channels + 4 IP channels  
5 technologies: IP, HDCVI, HDTVI, AHD and analogue CVBS cameras  
H.265 Pro+, H.265 Pro, H.265, H.264+, H.264, H.264 video formats  
4 BNC inputs (supports coax):  
HDCVI: 4MP, 1080P, 720P  
HDTVI: 8MP, 5MP, 4MP, 3MP, 1080P, 720P  
AHD: 5MP, 4MP, 1080P, 720P  
CVBS analogue: 960H, PAL/NTSC  
4 IP inputs (4+4), channel 1 up to 8MP  
Independent HDMI (2K) and VGA (1080P) outputs  
BNC video output  
Audio channels: 4 RCA inputs / 1 RCA output  
Bi-directional audio: via RCA audio channel  
1  
Recording resolution: 8MP, 5MP, 4MP, 3MP, 1080P, 720P, WD1, 4CIF, VGA, CIF  
Stream 1: 8MP (8 fps, 1 channel only), 5MP (12 fps), 4MP (15 fps), 3MP (18 fps), 1080P, 720P, WD1, 4CIF, VGA, CIF (25/30 fps)  
Stream 2: WD1, 4CIF, CIF (25/30 fps)  
4-channel synchronised playback  
Long distance HDTVI transmission: up to 1200 metres at 720P and 800 metres at 1080P  
Internal capacity for 1 SATA HDD up to 10TB (sold separately)  
Intelligent Search  
Supports multiple VCA (Video Content Analytics) events for both analogue and smart IP cameras  
Supports cross-line detection and intrusion detection on all channels, as well as sudden scene change detection on 2 channels  
4 alarm inputs / 1 alarm output  
Auto-adaptive RJ45 (10/100M) Ethernet network interface  
Network protocols: TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS  
Remote access for up to 32 users  
Onvif compatible  
P2P in the cloud, DDNS, DEMES, Push and zero channel  
Connections: 2 USB 2.0, 1 RS485 (half-duplex)  
Power supply: 48V DC, 1A  
Power consumption: ≤40W  
Supplies power to PoC cameras via coaxial cable  
Operating temperature: -10°C ~ +55°C  
Relative humidity: 10~90%.  
Dimensions: 315 (W) x 45 (H) x 242 mm (desktop)  
Weight: ≤1.5 kg