

# HYU-953

SF-IPD360-12Y

HYUNDAI

## IP fisheye dome HYUNDAI 12MP outdoor



- Dome fisheye IP HYUNDAI
- 12MP@20ips, H.265+/H.265
- ICR, 0.082/0.016 lux, IR 15m
- 2mm fixed lens
- Digital WDR, 3D-DNR, Defog, ROI
- IVS intelligence
- 1 input / 1 audio output
- 2 microphones + 1 speaker
- 1 input / 1 alarm output
- MicroSD slot, Onvif, RJ45 Gigabit, IP67, IK10, 12V/PoE



Reference / Model

HYU-953 / SF-IPD360-12Y

specs

**IP fisheye dome HYUNDAI 12MP outdoor****Reference / Model****HYU-953 / SF-IPD360-12Y**

1/1.7" 12-megapixel CMOS image sensor  
Resolution: 12MP (4000x3000), 9MP (3000x3000), 6.5MP (2560x2560), 720x720, VGA (640x480)  
Video compression H.265+, H.265, H.264+, H.264 and MJPEG  
Stream 1: 12MP (20fps), 9MP, 6.5MP (25fps)  
Stream 2: 720x720, VGA (25fps)  
Day/night mode with removable mechanical filter (ICR)  
0.082 lux F2.8 (color, AGC On), 0.016 lux F2.8 (B/W), 0 lux IR On  
IR illumination: 15 meters  
2mm fixed lens  
Horizontal viewing angle: 180°(wall mounted), 360°(ceiling mounted)  
Picture modes: BLC, HLC, Digital WDR, 3D-DNR, Defog  
4 fixed ROI zones on the main and secondary stream  
Video sensor and privacy masks  
Adjust saturation, brightness, contrast, sharpness, white balance, and gain control via client software or web browser  
Intelligence IVS: Line crossing detection, intrusion detection, area entry/exit detection, unattended baggage detection, object removal detection  
Audio exception detection  
1 input / 1 audio output  
Includes 2 microphones and speaker  
1 input / 1 alarm output  
MicroSD card slot up to 256GB (card not included)  
Network interface: RJ45 (10/100/1000M) self-adaptive  
Network protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour  
ONVIF (S/G), ISAPI compliant  
Up to 32 users and 20 simultaneous views  
Compatible with IE, Chrome and Firefox browsers  
Plug&Play connection with NEXTGEN NVR  
Compatible with DDNS DEMES  
Power: 12V DC (±20%) / PoE (802.3af)  
Consumption: 11W (12V) / 12W (PoE)  
Operating temperature -40°C ~ +60°C  
Humidity: <95% (non-condensing)  
Degree of protection IP67  
Vandal protection IK10  
metal casing  
Dimensions: 167.4 x 152.8 x 55mm  
Weight: 1.4kg