

HYU-404N

SF-IPMC102AW-2P / SF-IPMC103WA-2P

HYUNDAI

Mini Day/Night IP Camera

EMP Professional Line **STARLIGHT** **120 dB WDR** **H.265+** 

- HYUNDAI mini IP camera
- 2MP@25fps, H.265+/H.265
- ICR, 0.002 lux
- 3.7mm fixed lens
- WDR 120dB, 3D-DNR, ROI
- 1 input / 1 audio output
- Onvif
- Not suitable for outdoors



Reference / Model

HYU-404N / SF-IPMC102AW-2P / SF-IPMC103WA-2P

specs

Mini Day/Night IP Camera**Reference / Model****HYU-404N / SF-IPMC102AW-2P / SF-IPMC103WA-2P**

1/2.8" 2 Megapixel CMOS Image Sensor
Resolution: 1080P (1920x1080), 720P (1280x720), VGA (640x480), Q720P (640x360), QVGA (320x240)
Video compression H.265+, H.265, H.264+, H.264 and MJPEG
Stream 1: 1080P, 720P (25fps)
Stream 2: VGA, Q720P, QVGA (25fps)
Stream 3: 1080P, 720P, VGA, Q720P, QVGA (1fps)
0.002 lux F1.2 (color, AGC On), 0 lux IR On
3.7mm fixed lens
View Angle: 75.5°(H), 41.6°(V), 87.3°(D)
Image modes: BLC, HLC, WDR 120dB, 3D-DNR, Defog, Mirror
1 fixed ROI zone in main stream
Video sensor and privacy mask
Brightness, saturation, contrast and sharpness adjustment via client software or web browser
1 input / 1 audio output
Network interface: RJ45 (10/100M) self-adaptive
Network protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour, SSL /TLS
Compliant with ONVIF, ISAPI, SDK
Up to 32 users and 15 simultaneous views
Compatible with IE, Chrome and Firefox browsers
Plug&Play connection with NEXTGEN NVR
Compatible with DDNS DEMES
Power: 12V DC (±20%)
Consumption: 1.5W (12V)
Operating temperature -30°C ~ +60°C
Humidity: <95% (non-condensing)
Not suitable for outdoors
Dimensions: 31.5 (W) x 31.5 (H) mm
Weight: 93g