

64-channel IP NVR**H.265+**  **CVBS**  

- 64-channel IP NVR
- H.265+/H265 formats
- 32MP/24MP 8-channel recording
- 400/400 Mbps input/output
- 1 HDMI 8K, 1 HDMI 4K, 1 VGA and 1 BNC
- Bidirectional audio
- 16 inputs / 9 alarm outputs
- Supports 4 SATA HDD, 1 eSATA
- 2 RJ45 Gigabit, 2 USB, 2 RS485, 1 RS232
- 220V AC

**Reference / Model****HYU-1132 / HYU-1132**

64 IP camera inputs

Compression format H.265+, H.265, H.264+, H.264

Incoming bandwidth: 400 Mbps

Outgoing bandwidth: 400 Mbps

Video outputs:

1 HDMI 1 8K output (simultaneous with VGA output).

1 HDMI 2 4K output (independent of HDMI 1 and VGA outputs)

1 VGA 1080P output

1 BNC video output

Bi-directional audio: 1 RCA input / 1 RCA output

Recording resolution: 32MP, 24MP, 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF

Decoding capacity: 2 channels at 32MP (30 fps) + 2 channels at 8MP (30 fps), 10 channels at 8MP (30 fps), 20 channels at 4MP (30 fps), 40 channels 1080P at 30 fps

64-channel IP NVR

Reference / Model	HYU-1132 / HYU-1132
Simultaneous playback of 16 channels	
16 alarm inputs / 9 alarm outputs	
Supports 4 SATA HDD up to 16TB (HDD not included)	
1 eSATA port	
Stream encryption over TLS for more secure streaming service	
Dual verification support for playback and download	
Enables connection of solar powered camera via OTAP protocol	
Supports multiple VCA (Video Content Analytics) events	
Special configurable intelligent camera functions, such as VCA detection (motion, line crossing, intrusion, etc.), heat map, ANPR and people counting	
POS information overlay on live view and playback, and POS triggered recording and alarming	
Intelligent search	
Network interface with 2 auto-adaptive RJ45 (10/100/1000M) Ethernet ports	
Network protocols: TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS	
Up to 128 remote connections	
Compatible with web browsers	
Connections: 2 USB 2.0, 1 USB 3.0, 2 RS485 (half-duplex), 1 RS232	
Power supply: 100V ~ 240V AC, 50/60Hz	
Power consumption: ≤15W (without HDD)	
12V /1A power supply output (controlled by alarm output 9) for external alarm devices	
Operating temperature: -10°C ~ +55°C	
Relative humidity: 10~90%.	
Dimensions: 445 (W) x 75 (H) x 400 mm	
Weight: ≤5 kg	
Desktop or 1.5U rackmount installation	