

HYU-932

HYU-932

HYUNDAI

IP camera HYUNDAI Color View 2MP outdoor



- HYUNDAI NEXT GEN Color View IP Camera
- 2MP@25ips, H.265+/H.265
- Color 24/7, 0.001 lux, Smart Light 30m
- 2.8mm optics
- Digital WDR, 3D-DNR, 1 ROI
- RJ45, Onvif, IP67, 3AXIS, PoE.



Reference / Model	HYU-932 / HYU-932
-------------------	-------------------

Specifications

IP camera HYUNDAI Color View 2MP outdoor**Reference / Model****HYU-932 / HYU-932**

1/2.8" 2 megapixel CMOS sensor
Compression formats: H.265+, H.265, H.264+, H.264, MJPEG
Digital resolution: 1080P (1920x1080), 1.3MP (1280x960), 720P (1280x720), VGA (640x480), Q720P (640x360), QVGA (320x240)
Stream 1: 1080P, 1.3MP, 720P (25fps)
Stream 2: VGA, Q720P, QVGA (25fps)
24/7 color mode
Smart Light: White light with a range of 30 meters
0.001lux F1.0
2.8mm fixed lens
View Angle: 107°(H), 56°(V), 127°(D)
Picture modes: BLC, HLC, Digital WDR, 3D-DNR, Mirror
1 fixed ROI zone main stream
Video sensor and privacy mask
Image rotation, brightness, saturation, contrast, sharpness, gain control and white balance adjustment via client software and web browser
Network interface: RJ45 (10/100M)
Network protocols: TCP/IP, ICMP, HTTP, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP™, SMTP, IGMP, QoS, IPv6, UDP, Bonjour, SSL/TLS
ONVIF (S/G/T), ISAPI and SDK compliant
Up to 32 users and 6 simultaneous views
Remote viewing via IE, Chrome and Firefox browsers
Plug&Play connection with NEXTGEN NVR
Compatible with DDNS DEMES
Power: 12V DC (±25%), 0.3A
Consumption: 3.6W
Supports PoE (802.3af)
PoE consumption: 4.5W
Storage temperature -30°C ~ +60°C
Operating temperature -30°C ~ +60°C
Relative humidity: 95% (non-condensing)
Degree of protection IP67
metal casing
Dimensions: 68.4 (W) x 65.2 (H) x 161.1 mm
Weight: 420g
3AXIS: 0°~360°(PAN), 0°~90°(TILT), 0°~360°(ROT)