

HYU-408N

SF-IPB025WA-4E / SF-IPCV025WH-4

HYUNDAI

HYUNDAI NEXT GEN 4MP SMART IR IP CAMERA 30M IP67

4MP **Value Line**  **IP67**  **120 dB WDR** **H.265+** 

- HYUNDAI Next Gen IP bullet camera with Smart IR of 30m for outdoor
- 1/3 "CMOS of 4MP
- Dual stream
- Compression formats H.265 +, H.265, H.264 +, H.264 and MJPEG
- Resolution up to 4MP at 20ips
- ICR filter
- 0.02 lux F2.0
- 2.8 mm fixed lens (100 °)
- OSD, AWB, AGC, BLC, WDR 120dB, 3D-DNR, ROI, video sensor and privacy masks
- Onvif (S / G), ISAPI
- IP67
- 3AXIS
- 12V DC
- Supports PoE



Reference / Model

HYU-408N / SF-IPB025WA-4E / SF-IPCV025WH-4

specs

HYUNDAI NEXT GEN 4MP SMART IR IP CAMERA 30M IP67**Reference / Model****HYU-408N / SF-IPB025WA-4E / SF-IPCV025WH-4**

Image sensor 1/3 "4 megapixel CMOS
Resolution: 4MP (2560x1440), 3MP (2304x1296), 1080P (1920x1080), 720P (1280x720), VGA (640x480), QVGA (320x240)
Video compression H.265 +, H.265, H.264 +, H.264 and MJPEG
Stream 1: 4MP (20 ips), 3MP, 1080P, 720P (25 ips)
Stream 2: VGA, QVGA (25 ips)
Day / night mode with removable mechanical filter (ICR)
0.0028 lux F2.0 (color)
Smart IR: 30 meters
2.8mm fixed lens
Viewing angle: 100 ° (H), 55 ° (V), 117 ° (D)
Imaging modes: BLC, WDR 120dB, 3D-DNR
Image settings: Saturation, brightness, contrast, sharpness, gain and white balance adjustable through client software or web browser
Supports video sensor, 1 region of interest (ROI) per stream and privacy mask
Network interface: RJ45 (10 / 100M) self-adaptive
Network protocols: TCP / IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6 UDP, Bonjour
Remote viewing with browsers (IE8 +, Chrome 31.00 ~ 44, Firefox 30.0 ~ 51 and Safari 8.0+) and IOS and Android smartphone
ONVIF (Profile S / G) and ISAPI compliant
DDNS compliant
Up to 32 users
Up to 6 simultaneous views
Power supply: 12V DC (± 25%)
Consumption: 5W, 7W PoE
Supports PoE + (802.3 af, Class 3)
-30 ° C ~ + 50 ° C operating temperature
Humidity: <95% (non-condensing)
Degree of protection IP67
Metal and plastic housing
Dimensions: Ø70 x 172.7 mm
Weight: 280g
3AXIS: 0 ° ~ 360 ° (PAN), 0 ° ~ 180 ° (TILT), 0 ° ~ 360 ° (Rotation)