

HYU-732

SF-AC3002KMFD-IP

HYUNDAI

Standalone HYUNDAI Presence Control terminal with biometric fingerprint reading and MIFARE card reader



- Standalone HYUNDAI Presence Control terminal with biometric fingerprint reading and MIFARE card reader
- Up to 1,000 fingerprints, 1,000 cards, 1,000 users, 100,000 events and 50,000 attendance records
- It incorporates 2.4" screen
- TCP / IP communication
- Not suitable for outdoor use.



Reference / Model

HYU-732 / SF-AC3002KMFD-IP

2.4 "LCD display for sampling time, date, week and assistance information

Possibility of adding fingerprints to the system remotely

TCP / IP communication

Fast and accurate fingerprint recognition

Up to 1,000 users, 1,000 fingerprints and a maximum of 100,000 events

Autonomous operation: add user information, cards and fingerprints locally

Download USB support reports

Up to 32 normal shifts, up to 32 shift shifts and up to 32 vacation schedules can be configured

Supports 6 attendance states, start of the day, end of the day, departure from rest, entry of rest, start of overtime and end of overtime

Generate attendance reports automatically

Supports multiple languages: Spanish, Portuguese, French, Italian, English, etc.

Specs

Standalone HYUNDAI Presence Control terminal with biometric fingerprint reading and MIFARE card reader

Reference / Model	HYU-732 / SF-AC3002KMFD-IP
	Linux operating system
	2.4 "LCD screen
	Capacity of up to 1,000 cards / users
	Events: Up to 100,000 events
	Attendance records: Up to 50,000 records
	Capacity of up to 1,000 tracks
	Fingerprint recognition time: <1 second (1: N)
	FAR (False Acceptance Rate): ≤0.001%
	FRR (False Rejection Rate): ≤0.1%
	Fingerprint Recognizer: Optical Module
	The integrated card reader supports MIFARE cards
	Card reading range: 0 ~ 5 cm
	Non-Backlit Physical Button Keyboard
	Communication interface: TCP / IP (10 / 100Mbps)
	USB 2.0 port
	1 buzzer and 1 speaker
	Power: 5V DC / 1A
	Operating temperature of -10 ° C ~ + 55 ° C
	Operating Humidity: 10% ~ 90%, no condensation
	Dimensions: 155 (W) x 140 (H) x 30 mm