

HYUNDAI 5-in-1 16-channel ZVR



HDCVI™

HDTVI

AHD

CVBS

H.265+

**MOTION
DETECTION 2.0**

- HYUNDAI 16-channel 5-in-1 ZVR
- H.265 Pro+/H.265+ formats
- 16 BNC 1080P Lite channels + 2 IP 5MP channels
- 1080PLite@15ips recording
- Simultaneous HDMI and VGA 1080P outputs
- Bi-directional audio, audio over coaxial
- Supports 1 HDD 10TB, 1 RJ45, 2 USB



Reference / Model

HYU-992 / SF-XVR6116MS

ZVR 5-in-1 16-channel analogue HD + 2 IP channels

5 technologies: IP cameras, HDCVI, HDTVI, AHD and Analogue CVBS

Connectable to H.265 Pro+, H.265 Pro, H.265, H.264+, H.264, H.264 IP cameras

16 BNC inputs (supports coax)

2 IP inputs up to 5MP (16+2)

Simultaneous HDMI (1080P) and VGA (1080P) outputs

Audio channels: 1 RCA input / 1 RCA output

Bi-directional audio: via RCA audio channel 1

Supports audio over coaxial (16 inputs)

Recording resolution: 1080P Lite, 720P, 720P Lite, WD1, 4CIF, VGA, CIF

Main stream:

1080P stream: 1080P Lite, 720P Lite, WD1, 4CIF, VGA, CIF (15 fps)

720P stream: 720P, WD1, 4CIF, VGA, CIF (15 fps)

HYUNDAI 5-in-1 16-channel ZVR

Reference / Model	HYU-992 / SF-XVR6116MS
	SD stream: WD1, 4CIF, VGA, CIF (25/30 fps)
	Secondary stream:
	1080P/720P stream: CIF, QVGA (15 fps)
	SD stream: CIF, QVGA (25/30 fps)
	16-channel synchronised playback
	Internal capacity for 1 SATA HDD up to 10TB (sold separately)
	Intelligent Search
	Motion detection based on deep learning 2.0, can classify people and vehicles and minimise false alarms caused by lights or objects such as leaves
	Auto-adaptive RJ45 (10/100M) Ethernet network interface
	Network protocols: TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP, HTTPS
	Remote access for up to 128 users
	P2P in the cloud, DDNS DEMES, Push and zero channel
	Connections: 2 USB 2.0
	Power supply: 12V DC, 1.6A
	Power consumption: $\leq 7W$
	Operating temperature: $-10^{\circ}C \sim +55^{\circ}C$
	Relative humidity: 10~90%.
	Dimensions: 285 (W) x 45 (H) x 210 mm (desktop)
	Weight: ≤ 1.8 kg