

HYU-765N

HYU-765N

HYUNDAI

Fixed dome 4 in 1 HYUNDAI NEXT GEN PRO series



- Fixed dome 4 in 1 HYUNDAI NEXT GEN PRO series
- Smart IR up to 40 meters
- 2 megapixel CMOS
- 1080P (1920x1080) resolution at 25 ips
- 2.8 mm (106.4 °) fixed lens
- Switchable 4-in-1 video output
- ICR filter
- OSD menu control via coaxial cable (UTC)
- Digital WDR, 2D-DNR
- It incorporates a microphone
- Supports coaxial cable audio transmission (only compatible with ZVR HYUNDAI with audio)
- Metal and plastic housing
- Degree of protection IP67
- 3AXIS
- 12V DC



Reference / Model

HYU-765N / HYU-765N

Specs

2 megapixel CMOS sensor

Digital resolution: 1080P (1920x1080)

Images per second:
TVI: 1080P (25/30 ips)
AHD: 1080P (25/30 ips)
CVI: 1080P (25/30 ips)
CVBS: PAL / NTSC

Switchable 4-in-1 video output (HDCVI, HDTV I, AHD, CVBS)

Removable mechanical filter

0.01 lux F1.2 (color) / 0 lux IR On

Smart IR: 40 meters

2.8mm fixed lens

Viewing angle 106.4 ° (H), 57.9 ° (V), 124.6 ° (D)

Fixed dome 4 in 1 HYUNDAI NEXT GEN PRO series

Reference / Model	HYU-765N / HYU-765N
Automatic and manual white balance	
Automatic gain control	
Backlight compensation: BLC, HLC	
Digital WDR	
2D digital noise reduction	
Brightness and sharpness adjustment	
Mirror mode	
Incorporates microphone	
Supports coaxial cable audio transmission (only compatible with ZVR HYUNDAI with audio)	
Power supply: 12V DC ($\pm 25\%$)	
Consumption: Max. 3.7W	
-40 ° C ~ + 60 ° C operating temperature	
Relative humidity: <90% (non-condensing)	
Degree of protection IP67	
Metal and plastic housing	
Dimensions: $\varnothing 109.8 \times 91$ mm	
Weight: 300g	
3AXIS: 0 ° ~ 360 ° (PAN), 0 ° ~ 75 ° (TILT), 0 ° ~ 360 ° (Rotation)	