

HYU-1077

HYU-1077

HYUNDAI

HYUNDAI multifunction 5-in-1 CCTV tester

- 5 in 1 multifunctional CCTV monitor with 7" retina touch screen with CVI/TVI/AHD cameras images test up to
- Incorporates dual band WiFi (creates access point)
- Audio input/output
- PTZ control
- UTP test
- PoE output
- 24V power output
- Onvif support
- HDMI 4K input/output
- 12V DC.



Reference / Model

HYU-1077 / HYU-1077

5-in-1 Multifunction CCTV Tester (CVBS, CVI, TVI, AHD, IP)

7" retina touch screen (1280x800 pixels)

Supports 8K and H.265/H.264 decoding with main stream display

HDMI input, support 4K resolution (30 fps)

HDMI output, supports up to 4K (3840x2160), 30 fps

Dual IP/analog test (simultaneous IP and analog camera test)

IP discovery, auto search IP address

Drop-down menu, menu accessible via shortcut key

Built-in WiFi: Allows to receive images from WiFi cameras and supports WiFi hotspot creation

Test CVI/TVI/AHD camera images up to 4K/8MP

BNC attenuation test

AHD/CVI/TVI camera test supports image capture, video recording and playback, and 4X zoom.

CVBS loop test: Transmits or receives analog video signal

HYUNDAI multifunction 5-in-1 CCTV tester

Reference / Model	HYU-1077 / HYU-1077
	Onvif IP camera test, supports 4K resolution
	Analog camera image display: automatically adapts to PAL and NTSC formats
	Fast Onvif: One keystroke to generate a test report
	Connection of IP cameras via RJ45 and WiFi, supports 1080p
	Real-time display
	PTZ control, image captures, video recording, recorded video playback
	TV output with color bar generator
	RJ45 cable TDR testing, cable quality testing
	PoE voltage measurement, PING test, IP address scanning, port flashing, etc.
	Built-in dual band WiFi 150Mbps
	WiFi Analyzer
	TesterPlay: Tester, android version cell phone, PC screen at the same time
	MicroSD card slot
	2 RJ45 Gigabit network ports
	48V DC PoE output: Supplies temporary power to PoE cameras
	24V /2A power output
	Audio input/output
	LED flashlight, calculators, players and other tools/applications
	Power: 12V DC /3A; 24V DC, 2A; 5V DC, 2A
	Built-in 7.6V, 7800mAh lithium polymer battery with 16 hours of battery life
	Fast battery charging
	Working temperature: -10°C ~ +50°C
	Dimensions: 255 x 160 x 46 mm
	Weight: 950 g
	Anti-sunlight cover
	Apps included: EVOPLUS, HYUVMS, ASMS, HYU CONNECT, HYUPLUS