

DS-PEA4H-10 Panic Alarm Master Station

The DS-PEA4H-10 master station supports functions such as live view, intercom, device call, etc. It is equipped with 10.1-inch high definition touch screen that displays flat-design interface. The master station applies to security areas such as school, square, hospital, shopping mall, station, market, park, etc.



Key Features

- Rotatable 2 MP built-in camera, which is available for privacy protection
- Video intercom between general/ pole/ box panic alarm station and master station. Receives and displays alarm information
- Supports device escrow via assistant station
- Real-time intercom, monitoring, group broadcast, quick dialing, call forwarding, call waiting, etc.
- VGA and HDMI video output
- Auto noise suppression and auto echo cancellation
- One-piece toughened glass panel, and multi-angle adjustable aluminum alloy bracket

Available Models

DS-PEA4H-10



Specifications

Panic Alarm Master Station		
Video	Camera	CMOS, 2 MP
	Resolution	1920 × 1080
	Frame rate	PAL: 25 FPS, NTSC: 30 FPS
Display	Screen	10.1 inch colorful TFT LCD, 1280 × 800
	Operation mode	Touch screen, and mechanical key
	User interface	Flat design
Audio	Audio input	Built-in microphone, handset, and mic support
	Audio output	Built-in loudspeaker, and handset
	Audio encoding/decoding standard	G.711U, G726, AAC, and Opus
	Audio compression code rate	64 Kbps, 32 Kbps, and 16 Kbps
Network	Ethernet	10 M/100 M/1000 M self-adaptive
	Network protocol	TCP/IP, HIK-SIP, and RTSP
Interface	Network interface	1 RJ45, 10 M/100 M/1000 M self-adaptive
	RS-485	2, RS-485 half-duplex interface
	I/O input	4
	I/O output	4, relay output
	RJ11	1, for handset
	VGA output	1, for display user interface, which can be used synchronously with HDMI
	HDMI output	1, for display user interface, which can be used synchronously with VGA
	Micro SDXC	1, Micro SDXC (≤ 128 GB)
	USB	1, USB 3.0 1, USB 2.0
Others	Power	12 VDC, PoE (IEEE 802.3 at/af)
	Consumption	≤15 W
	Operating Temperature	-10 °C to 55 °C
	Operating Humidity	10% to 90%
	Dimension(L×H×D)	with handset: 361mm (14.2 inch) × 65mm (2.6 inch) × 197mm (7.8 inch) without handset: 291mm (11.5 inch) × 41mm (1.6 inch) × 197mm (7.8 inch)
	Weight	≤2.5 kg (88.2 oz)

Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com