

HYU-747

HYU-747

HYUNDAI

HYUNDAI NEXTGEN thermal bullet + visible camera Thermal-Line series with IR of 40 m, for outdoors



- HYUNDAI NEXTGEN thermal bullet + visible camera Thermal-Line series with IR of 40 m, for outdoors
- Visible camera with 1/2.8" CMOS of 2 MP
- 8 mm visible lens
- Thermal camera with resolution 384 x 288, 15 mm thermal lens
- Detection of people up to 441 meters and vehicles up to 1353 meters
- Digital WDR, 3D-DNR
- Intelligent detection (VCA)
- IP / ANALOG video output
- Audio: 1 input / 1 output
- Alarm: 2 inputs / 2 outputs
- MicroSD slot Onvif, API, ISAPI
- Lightning-proof 6KV
- IP66 24V AC, 12V DC
- PoE +.



Reference / Model

HYU-747 / HYU-747

FPA sensor (focal plane matrices) not cooled with vanadium oxide

384x288 thermal resolution

Pixel Interval: 17µm

Thermal sensitivity (NETD): <40 mk (@ 25 ° C, f / 1.0)

Spectrum range: 8 µm ~ 14 µm

Focal length (thermal): 15 mm

Viewing angle (thermal): 24.2 ° x 18.4 °

Minimum focusing distance of 2.5 meters

Effective distance in people: Detection (441 m), recognition (110 m), identification (55 m)

Effective distance in vehicles: Detection (1353 m), recognition (338 m), identification (169 m)

15 adjustable color palettes, 3D-DNR

Image detail enhancement

Supports 4 types of VCA rules (intrusion, line crossing, region input and region output), maximum 8 rules

HYUNDAI NEXTGEN thermal bullet + visible camera Thermal-Line series with IR of 40 m, for outdoors

Reference / Model	HYU-747 / HYU-747
Temperature range from -20 ° C ~ + 150 ° C	
Temperature accuracy of ± 8 ° C	
Supports 3 types of temperature measurement rules, 21 rules (10 points, 10 regions and 1 line)	
Supports 10 fire detection points	
Visible camera	
Image sensor (visible camera) CMOS 1 / 2.8 Progressive Scan 2 megapixels	
Effective pixels: 1920 x 1080	
40 meter infrared lighting	
Minimum illumination: 0.002 lux F1.5 (color) / 0.0002 lux F1.5 (B / W) / 0 lux IR On	
Focal length (visible optics): 8 mm	
Viewing angle (visible optics): 40 ° x 22.4 °	
Removable mechanical filter	
Digital WDR	
Supports merging of bi-spectrum images, image preview in image and image change	
IP communication and integration	
Compression formats: H.265 + / H.265 / H.264 / H.264 + / MJPEG (baseline / main / high profile)	
Stream 1 thermal camera: 384x288 at 50 fps	
Stream 2 thermal camera: 384x288 at 50 fps	
Stream 1 visible camera: 1080P / 1.3MP / 720P at 25 fps	
Stream 2 visible camera: D1 / CIF / QCIF at 25 fps	
Audio compression: G.711u / G.711a / G.722.1 / MP2L2 / G.726 / PCM	
1 RJ45 10 / 100M auto-adaptive port	
Protocols: IPv4 / IPv6, HTTP, HTTPS, 802.1x, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP,	
RTCP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE	
Up to 20 simultaneous visualizations	
Up to 32 users, 3 levels: administrator, operator, user	

HYUNDAI NEXTGEN thermal bullet + visible camera Thermal-Line series with IR of 40 m, for outdoors

Reference / Model	HYU-747 / HYU-747
Compatibility API, ONVIF, API, ISAPI, and third-party management gateway	
Compatible with IE9 +, Chrome31-44, Firefox30-51, Safari5.02 + (Mac) browsers	
2 inputs / 2 alarm outputs	
1 input / 1 audio output	
Reset button	
MicroSD / SDHC / SDXC card slot (up to 128 GB), with support for manual or alarm recording	
BNC output 1.0V [p-p] / 75Ω (PAL / NTSC)	
Electric and environmental	
Power supply: 24V AC, 12V DC, PoE + (802.3at, class 4)	
Consumption: max. 20W	
Operating temperature of -40 ° C ~ + 60 ° C	
Relative humidity: ≤90% (without condensation)	
IP66 protection degree	
6KV lightning-proof	
Physical characteristics	
Metal housing	
Dimensions: 93 (W) x 93 (H) x 314 mm	
Weight: 1.55 kg	
Wall mount included	
Note: The actual distance values shown are nominal values and should be used as an estimate. Check with your salesperson for the recommended detection distances with our Vaelsys perimeter system.	