

HYU-970

SF-IPD934CW-4P

HYUNDAI

HYUNDAI ColorView 4MP outdoor IP dome

4MP **Value Line** **IP67** **STARLIGHT FULL-Color** **120 dB WDR** **H.265+**

- HYUNDAI ColorView IP Dome
- 4MP@20ips, H.265+/H.265
- Colour 24/7, 0.001 lux, white light 30m
- 2.8mm fixed optics
- WDR 120dB, 3D-DNR, ROI
- RJ45, IP67, 3AXIS, 12V/PoE.



Reference / Model

HYU-970 / SF-IPD934CW-4P

4-megapixel 1/3" CMOS image sensor

Resolution: 4MP (2560x1440), 1080P (1920x1080), 720P (1280x720), VGA (640x480), Q720P (640x360)

H.265+, H.265, H.264+, H.264, H.264 and MJPEG video compression

Stream 1: 4MP (20 fps), 1080P, 720P (25/30 fps)

Stream 2: 720P, VGA, Q720P (25/30 fps)

24h colour mode

0.001 lux F1.0 (colour, AGC On), 0 lux with white light On

White illumination: 30 metres

2.8 mm fixed optics

Angle of view: 96°(H), 52°(V), 113°(D)

Imaging modes: BLC, HLC, WDR 120dB, 3D-DNR

1 fixed ROI zones for main stream

HYUNDAI ColorView 4MP outdoor IP dome

Reference / Model	HYU-970 / SF-IPD934CW-4P
	Image rotation, saturation, brightness, contrast, contrast, sharpness, mirror mode, white balance and gain control adjustable via client software or web browser
	4 privacy masks
	Network interface: RJ45 (10/100M) auto adaptive
	Network protocols: TCP/IP, ICMP, DHCP, DNS, DDNS, HTTP, HTTPS, RTP, RTSP, NTP, UPnP, IGMP, IPv6, UDP, QoS, Bonjour, FTP, 802.1X, SNTTP
	ISAPI, SDK support
	Up to 32 users
	Compatible with IE, Chrome and Firefox browsers
	Plug&Play connection with NVR NEXTGEN
	Compatible with DDNS DEMES
	Power: 12V DC ($\pm 25\%$) / PoE (802.3af)
	Power consumption: 5W (12V) / 6.5W (PoE)
	Operating Temperature $-30^{\circ}\text{C} \sim +60^{\circ}\text{C}$
	Humidity: $<95\%$ (non-condensing)
	IP67 protection rating
	Aluminium housing
	Dimensions: $\varnothing 121.5 \times 97.6$ mm
	Weight: 500 g
	3AXIS: $0^{\circ} \sim 355^{\circ}$ (PAN), $0^{\circ} \sim 75^{\circ}$ (TILT), $0^{\circ} \sim 355^{\circ}$ (Rotation)