

HYU-1119

HYU-1119

HYUNDAI

16-channel IP NVR



- HYUNDAI 16-channel IP NVR
- H.265+/H265 formats
- Up to 4 channels 24/32MP or 16 channels 12MP recording
- 160/256Mbps input/output
- Outputs VGA 1080P, HDMI 4K and BNC output
- Bidirectional audio
- Perimeter protection, facial recognition, ANPR, POS
- Motion detection 2.0
- 4 inputs / 1 alarm output
- Supports 2 HDD 14TB
- 220V AC, 1U rack



Reference / Model	HYU-1119 / HYU-1119
16 IP camera inputs	
H.265+, H.265, H.264+, H.264, H.264 compression format	
Incoming bandwidth: 160 Mbps	
Outgoing bandwidth: 256 Mbps	
Independent VGA 1080P and HDMI 4K video outputs	
BNC video output	
Output division: 1, 4, 6, 6, 8, 9, 9, 16	
Two-way audio: 1 RCA input / 1 RCA output	
Recording resolution: 32MP (max. 4 channels), 24MP (max. 4 channels), 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF	
AI in the recorder:	
Perimeter protection: 4 channels at 2MP with person and vehicle recognition.	
Facial recognition: 4 channels for video stream and 8 channels for facial comparison, up to 16 facial libraries and 50,000 facial images in total.	

16-channel IP NVR

Reference / Model	HYU-1119 / HYU-1119
Motion detection 2.0: All channels	
AI support from compatible cameras	
Perimeter protection: All channels	
Motion detection 2.0: All channels	
ANPR: All channels with license plate and vehicle attributes	
16-channel synchronized playback	
Decoding capacity:	
AI on: 20 channels 1080P 30 fps	
AI off: 32 channels 1080P 30 fps	
4 alarm inputs / 1 alarm output	
Internal capacity for 2 SATA HDD up to 14TB (sold separately)	
Supports multiple VCA (<i>Video Content Analytics</i>) events	
Intelligent search of selected area in the video and intelligent playback to improve playback efficiency	
POS information overlay on live display and playback	
POS-triggered recording and alarming	
Network interface with two auto-adaptive RJ45 (10/100/1000M) Ethernet ports	
Network protocols: TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS	
Onvif (S/G), SDK, ISAPI support	
Up to 128 remote connections	
Communication Ports: 1 USB 2.0 port, 1 USB 3.0 port	
Power supply: 100V ~ 240V AC, 50/60 Hz	
Power consumption: ≤30W (without hard disks)	
Operating temperature: -10°C ~ +55°C	
Relative humidity: 10 ~ 90%	
Dimensions: 385 (W) x 52 (H) x 317 mm	

16-channel IP NVR

Reference / Model**HYU-1119 / HYU-1119**

Weight: ≤2.5 kg

Desktop or 1U rackmount installation
