

SLA-T4680D/T4680DW/T4680DS

2M Door Jamb Lens Modules



SLA-T4680D
(black)



SLA-T4680DW
(white)



SLA-T4680DS
(silver)

Key Features

- Compatible with XNB-6001
- Max. 2Megapixel (1920 x 1080) resolution
- 4.6mm pinhole lens
- 0.06Lux@F2.5
- 8m cable
- Easy installation
- Flexible panning ± 30 degrees
- Multiple housing color options to match the door jamb
- Hidden security screw for discrete look

	SLA-T4680D	SLA-T4680DW	SLA-T4680DS	
VIDEO				
Imaging Device	1/2.8" 2M CMOS			
Total Pixels	1,945(H) x 1,109(V) 2.16M			
Effective Pixels	1,945(H) x 1,097(V) 2.13M			
Scanning System	Progressive Scan			
Min. Illumination	Color: 0.06Lux (F2.5) B/W: 0.06Lux (F2.5)			
S / N Ratio	50dB			
Wide Dynamic Range	120dB			
Day & Night	Electrical			
LENS				
Focal Length (Zoom Ratio)	4.6mm			
Max. Aperture	F2.5			
Angular Field of	H: 73° / V: 39° / D: 85°			
Min. Object Distance	0.98ft (0.3m)			
Lens Type	Pinhole			
Mount Type	RJ12 connected with main unit			
ENVIRONMENTAL				
Operating Temperature / Humidity	-10°C ~ +55°C (+14°F ~ +131°F) / Less than 90% RH			
Storage Temperature / Humidity	-50°C ~ +60°C (-58°F ~ +140°F) / Less than 90% RH			
MECHANICAL				
Color / Material	Lens	Black / Plastic	Black / Plastic	Black / Plastic
	Cable	Black	Black	Black
	Housing	Black	White	Silver
Dimensions (WxHxD)	Lens	Ø0.94" x 1.65" (Ø24 x 42mm)		
	Cable	314.96" (8m)		
Weight	0.68 lb (310g)			

* The latest product information / specification can be found at hanwha-security.com
 * Design and specifications are subject to change without notice.
 * Wisenet is the proprietary brand of Hanwha Techwin, formerly known as Samsung Techwin.

Dimensions

Unit: inch (mm)

