

- 4K HD solution
- · Using all-imported industrial-grade LED screen
- · Designed for CCTV
- · High brightness, high contrast, high definition
- Adapts to the latest 3D digital filtering and 3D digital noise reduction technology
- · Picture fast response
- · 178° wide viewing angle
- · Ensures that the image display is not deformed
- · 24/7 working status, working continuously for 5 years
- Metal chassis design, anti-static, anti-magnetic field, anti-interference, no radiation
- · Menu with convenient controller



















DIMENSIONS (MM)







INDUSTRIAL MONITOR 28" 4K

Version no.: 1.0 (Jan 2023) Page 1 of 2

Industrial Monitor 28" 4K



DISPLAY CHARACTERISTICS	
Mode name	LC-ME2801- 4K
Screen size	28"
Active display area (mm)	620.93mm(W)×341.3mm(H)
Display mode	16:9
Led type	TFT-LED
Resolution	3840 × 2160
Display colour	1.073G
Pixel pitch (mm)	0.1617(H)×0.1617(V)
Brightness (nits)	350cd/m ²
Contrast ratio	1000:1
Viewing angle	178(H)/178(V)
Response time	5ms
Backlight	LED

INPUT & OUTPUT		
HDMI 2.0	3	
DP	1	
USB	1	
Power	1	
Speaker	2x 3W(Stereo)	

VIDEO	
Colour system	PAL/NTSC/SECAM
OSD control	Auto adjust, Brightness, Contrast, Hori. / Vert. Position, Clock, Phase, Color, Language
3D comb filter	YES
Support Picture in Picture (PIP)	YES

POWER & Mount		
Power	AC100V~240V,50/60Hz	
Working temperature	30 to +85 °C	
Power consumption	<40W	
Menu	English, German, French	
Mounting/weight	VESA mount/7kg	
MTBF	50000Hours	
Accessories	Industrial PSU, screw, cable holder, quick start guide	



INDUSTRIAL MONITOR 28" 4K

Version no.: 1.0 (Jan 2023) Page 2 of 2