

HYU-755N

SF-NVR6104-4KE-4P / SF-NVR6104-4KE

HYUNDAI

HYUNDAI NEXTGEN 4-channel IP NVR



- HYUNDAI NEXTGEN 4-channel IP NVR
- H.265+/H.265/H.264+/H.264
- 4-channel synchronous playback
- Up to 8MP display
- 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc
- recording
- Up to 40 Mbps recording
- HDMI 4K and VGA 1080P output
- Bi-directional audio
- Supports 1 SATA HDD
- RJ45 Fast Ethernet
- Compatible, P2P, DDNS
- 12V DC
- 4 PoE+.



Reference / Model	HYU-755N / SF-NVR6104-4KE-4P / SF-NVR6104-4KE
4 IP channels up to 8MP	
Video compression: H.265+, H.265, H.264+, H.264	
HDMI video output (4K) and 1 VGA output (1080P)	
1 RCA input / 1 RCA audio output	
Bi-directional audio via RCA input/output	
Recording resolution: 4K/8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF	
Incoming bandwidth: 40 Mbps	
Outgoing bandwidth: 80 Mbps	
Decoding capacity: 1 channel at 8MP (25 fps), 5 channels at 1080P (25 fps)	
4-channel synchronised playback	
Internal capacity for 1 SATA HDD up to 8TB (sold separately)	
Supports VCA (video content analytics) events	

HYUNDAI NEXTGEN 4-channel IP NVR

Reference / Model	HYU-755N / SF-NVR6104-4KE-4P / SF-NVR6104-4KE
	Configurable intelligent camera functions such as VCA detection (motion, line crossing, intrusion, etc.), heat map, ANPR and people counting
	Supports intelligent search
	RJ45 Fast Ethernet (10/100Mbps) network port
	4 PoE ports (IEEE802.3af/at) with 25.5W output power per port for a total of 50W
	Network Protocols: TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS
	Up to 16 remote connections
	Remote access via iPhone/iPad, Android devices
	Multi-browser compatibility: Chrome, Firefox, Safari, IE
	P2P in the cloud, DDNS DEMES, Push and zero channel
	Plug&Play connection with NEXTGEN IP cameras
	Communication ports: 1 USB 3.0 port, 1 USB 2.0 port
	Power supply: 48V DC, 1.3A
	Power consumption: ≤10W (excluding disks and with PoE disabled)
	Operating temperature from -10°C ~ +55°C
	Relative humidity 10% ~ 90%.
	Dimensions: 320 (W) x 48 (H) x 240 mm
	Weight: ≤1 kg
	Desktop installation