

HYU-1083

HYU-1083

HYUNDAI

4 in 1 5MP outdoor camera



- HYUNDAI 4 in 1 camera
- 5MP@20ips (TVI/AHD), 4MP@25/30ips (TVI/CVI/AHD)
- Switchable 4 in 1 output
- ICR, 0.02 lux, Smart IR 40m
- 3.3~12mm varifocal optics
- Digital WDR, 2D/3D-DNR
- IP66, 3AXIS



Reference / Model

HYU-1083 / HYU-1083

5-megapixel 1/2.5" Sony CMOS sensor

Digital resolution:

HDCVI: 4MP (2560x1440) @25/30 ips

HDTVI: 5MP (2560x1936) @20 fps

AHD: 5MP (2560x1936) @20 ips

Analog CVBS: 960H @25/30 fps

4 in 1 output (switchable from OSD): HDCVI / HDTVI / AHD / CVBS 960H

Removable mechanical filter

0.02 lux F1.2 color (AGC On) / 0 lux IR On

Optical glass window with higher light transmittance

Smart IR: 20 led SMD array, 30~40 meters

3.3 ~ 12 mm varifocal optics

OSD via coax (only CVI, TVI, AHD modes, 300 meters range)

4 in 1 5MP outdoor camera

Reference / Model	HYU-1083 / HYU-1083
Auto white balance	
Auto gain control	
Picture modes: BLC, HLC, digital WDR, 2D/3D-DNR, Defog, mirror mode.	
Videosensor	
Power supply: 12V DC ($\pm 10\%$)	
Power consumption: <8W	
Working temperature: $-20^{\circ}\text{C} \sim +60^{\circ}\text{C}$	
Relative humidity: 10%~90%.	
Degree of protection: IP66	
Metal housing	
Dimensions: 262,3 x 75 x 73 mm	
3AXIS bracket with internal cable routing	