

# HYU-1062

HYU-1062

HYUNDAI

## 4MP solar IP camera with 4G



- HYUNDAI Solar IP Camera with 4G
- 4MP@12/15ips, H.265+/H.265
- ICR, 0.01 lux, Smart IR 30m
- 4mm fixed optics
- Digital WDR, 3D-DNR, ROI
- Detection of people and vehicles
- Two-way audio with microphone and speaker
- MicroSD slot, built-in 8GB eMMC, RJ45, IP67
- Autonomous with solar panel and battery



Reference / Model	HYU-1062 / HYU-1062
4 megapixel 1/3" CMOS image sensor	
H.265+, H.265, H.264+, H.264, H.264 and MJPEG video compression	
Resolution: 4MP (2560x1440), 1080P (1920x1080), 720P (1280x720), VGA (640x480), Q720P (640x360)	
Stream 1: 4MP, 1080P, 720P (12.5/15 fps)	
Stream 2: 720P, VGA, Q720P (12.5/15 fps)	
Day/night mode with removable mechanical filter (ICR)	
0.01 lux F1.6 (color, AGC On), 0 lux IR On	
Smart IR: up to 30 meters	
4 mm fixed optics	
Angle of view: 79°(H), 43°(V), 93°(D)	
Imaging modes: BLC, HLC, digital WDR, 3D-DNR	
1 fixed ROI zone in main stream	

**4MP solar IP camera with 4G**

Reference / Model	HYU-1062 / HYU-1062
	Adjustment of rotation, saturation, brightness, contrast, contrast, sharpness, white balance and gain control via client software or web browser
	People detection via PIR+Radar motion sensor with up to 12 meters range
	Bi-directional audio: incorporates microphone and speaker
	Ambient noise filter
	Built-in 8GB of eMMC storage with 5GB available for recording
	MicroSD card slot up to 256GB (card not included)
	Reset button
	Network interface: RJ45 (10/100M) auto adaptive
	Network protocols: TCP/IP, ICMP, HTTP, HTTP, DHCP, DNS, RTP, RTSP, RTCP, NTP, IGMP, QoS, UDP
	Onvif (S/G/T), ISAPI, SDK support
	Up to 32 users and 6 simultaneous views
	Compatible with IE, Chrome and Firefox browsers
	Plug&Play connection with NVR NEXTGEN
	Compatible with DDNS DEMES
	4G mobile communication (LTE-TDD/LTE-FDD/LTE-FDD/TD-SCDMA)
	Stand-alone operation with built-in solar panel and battery
	Power supply: 12V DC (for debugging only)
	Consumption: 1.85W (4G) / 80mW (standalone scenario) / 7W (maximum)
	Operating temperature from 0°C ~ +50°C
	Humidity: <95% (non-condensing)
	IP67 degree of protection
	Plastic housing
	Dimensions: 292,4 (W) x 188,7 (H) x 213,7 mm
	Gross weight: 2.07 kg
	Net weight: 1.42 kg

**4MP solar IP camera with 4G**

---

**Reference / Model****HYU-1062 / HYU-1062**Solar panel angle adjustment: -45°~+45°(TILT), -30°~+30°(ROTATION)

---