

# HYU-614

HYU-614

HYUNDAI

## 2MP IP Alsense dome with IR of 30m, vandal protection suitable for outdoors



- 2MP IP Alsense dome with IR of 30m, vandal protection suitable for outdoors
- H.265/H.264/MJPEG
- 1/2,8" CMOS, 2MP
- 2MP@25 fps
- ICR
- 0,009 lux
- 2,8 mm lens (108°)
- OSD, AGC, BLC, real WDR 120dB, 3D-DNR, 1 fixed ROI
- IVS
- Reset button
- MicroSD
- Onvif, ISAPI
- IP67, IK10
- 3AXIS
- 12V DC
- PoE.



Reference / Model	HYU-614 / HYU-614
Up to 2MP at 25 fps	
2.8 mmlens	
H.265	
WDR 120dB, BLC, 3D-DNR, ROI	
False alarm filter by objective classification (Alsense)	
Infrared illumination of up to 30 meters	
MicroSD card slot up to 128GB (card not included)	
IP67	
IK10 vandal protection	
PoE supported	

## 2MP IP Alsense dome with IR of 30m, vandal protection suitable for outdoors

Reference / Model

HYU-614 / HYU-614

### Especificaciones

- 1/2.8" CMOS sensor 2MP
- Digital resolution: 1080P (1920x1080), 1.3MP (1280x960), 720P (1280x720), etc.
- H.265 / H.264 / MJPEG compression format
- Main Stream: 1080P / 1.3MP / 720P (25 ips)
- Secondary Stream: D1 / VGA / CIF (25 ips)
- Day/night mode with removable mechanical filter
- Infrared illumination: 30 meters
- Minimum illumination: 0.009 lux F1.6 color (AGC On)
- 2.8 mm lens
- Angle of vision: 108 ° (H), 58 ° (V)
- OSD menu
- White balance
- AGC automatic gain control
- Compensation of BLC backlights
- Real WDR 120dB
- Digital reduction of 3D noise
- 1 fixed ROI main stream and secondary stream
- Adjustment of brightness, saturation, contrast, sharpness, gain control and white balance through client software and web browser
- Smart functions: Detection of line crossing, intrusion detection, detection of entry or exit to region, false alarm filter by objective classification
- Reset button
- MicroSD / SDHC / SDXC card slot up to 128GB (card not included)
- Network interface: RJ45 (10/100 Base-T)
- Network protocols: TCP / IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1x, QoS, IPv6, UDP, Bonjour
- Compatible with ONVIF (Profile S, G), ISAPI
- Plug & Play connection with NVR NEXTGEN
- Compatible with DDNS DEMES
- Power: 12V DC
- Consumption: 0.6A, max. 7W
- Supports PoE 802.3af, max. 8.5W
- Operating temperature of -30 ° C ~ + 50 ° C
- Humidity: 95% (without condensation)
- IP67
- IK10 vandal protection
- Metal housing
- Dimensions: Ø121.4 x 92.2 mm
- Weight: 600 g
- 3AXIS: 0 ° ~ 355 ° (PAN), 0 ° ~ 75 ° (TILT), 0 ° ~ 355 ° (Rotation)
- Power supply is not included