HIKVISION

DS-D5024FC 23.6" Monitor

Overview


DS-D5024FC is a reliable surveillance display with LED backlit technology, excellent color reduction and image processing, truly display the video details. Multiply interfaces are able to meet various surveillance environments, and build-in speaker is convenient to audio play. DS-D5024FC is an ideal choice for security and surveillance application.

key Features

- LED backlit technology with full HD 1920×1080@60Hz
- Wide view angle: 170°(H)/160°(V)
- Image processing: 3D comb filter, 3D De-interlace,
 3D noise reduction
- Multiply interface: HDMI, VGA, BNC input, BNC output, audio in
- Support analog signal input
- Build-in speaker
- High reliable components for 7×24 working
- VESA stand bracket
- Green energy: Enter standby mode while no signal input

Model:

DS-D5024FC



NO.	Description
1	3.5mm headphone interface
2	AUDIO
3	BNC in and out
4	VGA: VGA Analog Signal Input
5	HDMI: HDMI Digital Signal Input



Interfaces

DS-D5024FC 23.6" Monitor



Specification

Model	DS-D5024FC
Display	
Display Type	LED-Backlit
Screen Size	23.6"
Pixel Pitch(H×V)	0.2715mm ×0.2715mm
Max Resolution	1920×1080
Brightness	250cd/m2 (Typical)
Contrast	1000:1(Typical) DCR 30,000,000:1
Response Time	5ms
Color	16.7M
Viewing Angle	Horizontal 170°, Vertical 160°
Interface	
номі	1
VGA	1
BNC	In $ imes$ 1, Out $ imes$ 1
Audio	
Audio Input	1x 3.5 mm mini-jack , 1x RCA type
Speaker	2*2W
Mounting	
VESA	100mm × 100mm
General	
Power Supply	AC 100~240V
Consumption	< 30W(on) < 0.5W(Standby)
Operation Temperature	0°C ~ 40 °C
Operating Humidity	10%~85% (No Condensation)
Storage Temperature	-20°C ~ 60°C
Storage Humidity	5%~95% (No Condensation)
Dimension (W×H×D)	561x339x218.5 (mm) 22.1x13.3x8.6(inch)
Weight	6.0Kg(Gross weight) , 5.1(Net weight)
Included Accessories	Power cord x 1, VGA cable x 1, User manual x 1, warranty card x 1, base bracket x 1



DS-D5024FC 23.6" Monitor



Dimension

