

# HYU-1030

SF-IPPT404ZWA-4E

HYUNDAI

## 4MP outdoor PTZ IP camera



- HYUNDAI Value Line IP PTZ Camera
- 4MP@20ips, H.265+/H.265
- ICR, StarLight 0.007 lux, Smart IR 50m
- Motorised optics 2.8 ~12 mm
- WDR 120dB, 3D-DNR, ROI
- Pan&Tilt: -100°~+100°(H), -20°~45°(V)
- Built-in microphone
- MicroSD slot, RJ45, IP66, 12V/PoE.



### Reference / Model

HYU-1030 / SF-IPPT404ZWA-4E

4-megapixel 1/3" CMOS image sensor

Resolution: 4MP (2560x1440), 1080P (1920x1080), 720P (1280x720), VGA (640x480), Q720P (640x360)

H.265+, H.265, H.264+, H.264, H.264 and MJPEG video compression

Stream 1: 4MP (20 fps), 1080P, 720P (25/30 fps)

Stream 2: 720P, VGA, Q720P (25/30 fps)

Day/Night mode with removable mechanical filter (ICR)

0.007 lux F1.6 (colour), 0 lux IR On

Smart IR: 50 meters (EXIR 2.0)

2.8 ~ 12 mm motorized optics

Viewing angle: 96.7°~29.7°(H), 51.7°~16.7°(V), 114.3°~34°(D)

Picture modes: BLC, HLC, WDR 120dB, 3D-DNR.

1 fixed ROI zone for the main stream

**4MP outdoor PTZ IP camera**

Reference / Model	HYU-1030 / SF-IPPT404ZWA-4E
Mirror mode, saturation, brightness, contrast, sharpness, gain and white balance adjustable via client software or web browser	
4 privacy masks	
Positioner: -100°~+100°(H), -20°~45°(V)	
Built-in microphone	
MicroSD card slot for up to 256GB (card not included)	
Network interface: RJ45 (10/100M) self-adapting	
Network protocols: TCP/IP, ICMP, DHCP, DNS, DDNS, HTTP, HTTPS, RTP, RTSP, NTP, UPnP, IGMP, IPv6, UDP, QoS, Bonjour, FTP, 802.1x, SMTP	
Onvif (S/G), ISAPI, SDK support	
Up to 32 users and 6 remote views	
Compatible with IE, Chrome and Firefox browsers	
Plug&Play connection with NVR NEXTGEN	
Compatible with DDNS DEMES	
Power supply: 12V DC (±25%) / PoE (802.3af)	
Power consumption: 11W (12V) / 12.5W (PoE)	
Operating Temperature -30°C ~ +60°C	
Humidity: <95% (non-condensing)	
IP66 degree of protection	
Metal and plastic housing	
Dimensions: 105 (W) x 197,1 (H) x 225,4 mm	
Weight: 900 g	