

HYU-1070

SF-NVR6208-4KE-8P

HYUNDAI

HYUNDAI 8-channel IP NVR with PoE

BMP Professional Line H.265+  **MOTION DETECTION 2.0**

- HYUNDAI IP NVR 8 channels
- H.265+/H265/H.264+/H.264
- Up to 80/80Mbps input/output
- HDMI (4K) and VGA (1080P) outputs
- Bidirectional audio
- Motion detection 2.0
- Supports 1 SATA HDD, 1 RJ45, 2 USB
- 48V DC, 8 PoE+ ports



Reference / Model

HYU-1070 / SF-NVR6208-4KE-8P

8 IP camera inputs

H.265+, H.265, H.264+, H.264, H.264 compression format

Incoming bandwidth: 80 Mbps

Outgoing bandwidth: 80 Mbps

Simultaneous HDMI (4K) and VGA (1080P) video outputs

Two-way audio: 1 RCA input / 1 RCA output

Recording resolution: 8MP, 6MP, 5MP, 4MP, 4MP, 3MP, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF

Decoding capacity: 6 channels 1080P (30 fps), 3 channels 4MP (30 fps), 1 channel 8MP (30 fps)

8-channel synchronized playback

Supports 1 SATA HDD up to 8TB (HDD not included)

4-channel 2.0 motion detection with human and vehicle classification

Intelligent search

Auto-adaptive RJ45 (10/100M) Ethernet network interface

HYUNDAI 8-channel IP NVR with PoE

Reference / Model	HYU-1070 / SF-NVR6208-4KE-8P
Network protocols: TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS	
Up to 32 remote connections	
Connections: 2 USB 2.0	
8 PoE ports (10/100Mbps, 802.3af/at)	
75W PoE delivery	
Power supply: 48V DC, 1.88A	
Consumption: ≤10W (without HDD / without PoE)	
Operating temperature: -10°C ~ +55°C	
Relative humidity: 10~90%.	
Dimensions: 320 (W) x 48 (H) x 240 mm	
Weight: ≤1 kg	
Desktop installation	