

DOMO IP HYUNDAI NEXT GEN 4MP SMART IR 40M IP67



H.265+



- HYUNDAI Next Gen IP fixed dome with Smart IR 40m for outdoor use
- CMOS 1/3" 4MP
- Triple Stream
- H.265+, H.265, H.264+, H.264 and MJPEG compression formats
- Resolution up to 4MP at 25ips
- ICR filter
- 0.005 lux F1.6
- 2.8~12mm (95.8°~29.2°) motorized optics
- OSD, AWB, AGC, BLC, WDR 120dB, 3D-DNR, ROI, video sensor and privacy masks
- IVS intelligence
- Face detection
- Two-way audio
- 1 input / 1 output alarm
- Onvif (S/G), ISAPI
- IP67
- 3AXIS
- 12V DC
- Supports PoE



Reference / Model

HYU-917 / SF-IPD825ZWA-4P-HV

4 megapixel 1/3" CMOS image sensor

Resolution: 4MP (2688x1520), 1080P (1920x1080), 720P (1280x720), VGA (640x480)

H.265+, H.265, H.264+, H.264 and MJPEG video compression

Stream 1: 4MP, 1080P, 720P (25 fps)

Stream 2: VGA (25 fps)

Stream 3: 720P, VGA (25 fps)

Day/Night mode with removable mechanical filter (ICR)

0.005 lux F1.6 (color), 0 lux IR On

Smart IR: 40 meters

2.8 ~ 12 mm motorized optics

Angle of view: 95.8°~29.2°(H), 50.6°~16.4°(V), 114.6°~33.4°(D)

DOMO IP HYUNDAI NEXT GEN 4MP SMART IR 40M IP67**Reference / Model****HYU-917 / SF-IPD825ZWA-4P-HV**

Picture modes: BLC, HLC, WDR 120dB, 3D-DNR.

Image settings: Rotation, mirror, privacy mask, saturation, brightness, contrast, sharpness, gain, and white balance adjustable via the client software or web browser

Supports video sensor, 1 region of interest (ROI) per stream, and privacy mask

Cross-line detection and intrusion detection

Face detection

MicroSD card slot for up to 256GB (card not included)

Two-way audio

1 alarm input / 1 alarm output

Network interface: RJ45 (10/100M) self-adapting

Network protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour, SSL/TLS, PPPoE

Remote viewing with browsers (IE10/11, Chrome 57.0+, Firefox 52.0+) and iOS and Android smartphones

ONVIF (Profile S/G), ISAPI, and SDK support

DDNS support

Up to 32 users

Up to 6 simultaneous displays

Power supply: 12V DC ($\pm 25\%$)

Power consumption: 10.5W, 12.5W PoE

Supports PoE+ (802.3 af, Class 3)

Operating temperature from -30°C ~ +60°C

Humidity: <95% (non-condensing)

IP67 protection rating

Aluminum housing

Dimensions: Ø153.3 x 111.6 (H) mm

Weight: 880 g

3AXIS: 0°~355°(PAN), 0°~75°(TILT), 0°~355°(Rotation)